

RF AMPLIFIER

MODEL *TM6442*

Available as: TM6442, 4 Pin TO-8 (T4)
 TN6442, 4 Pin Surface Mount (SM3)
 FP6442, 4 Pin Flatpack (FP4)
 BX6442, Connectorized Housing (H1)

Features

- High Output Power: +22 dBm Typical
- High Dynamic Range IP3= 37 dBm
- Operating Temp. - 55 °C to +85 °C
- Environmental Screening Available

Specifications

CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	20 - 400 MHz	20 - 400 MHz
Gain (dB)	14	12.5 Min.
Power @ 1 dB Comp. (dBm)	+22	+19.0 Min.
Reverse Isolation (dB)	- 19	- 17 Max.
VSWR In	1.15:1	2.0:1 Max.
Out	1.25:1	2.0:1 Max.
Noise figure (dB)	4.5	6.0 Max.
Power Vdc	+15	+15
mA	62	85 Max.

Note: Care should always be taken to effectively ground the case of each unit.


Typical Intermodulation Performance at 25 °C

Second Order Harmonic Intercept Point +57 (Typ.)
 Second Order Two Tone Intercept Point +51 (Typ.)
 Third Order Two Tone Intercept Point +37 (Typ.)

Maximum Ratings

Ambient Operating Temperature -55°C to + 100 °C
 Storage Temperature -62°C to + 125 °C
 Case Temperature + 125 °C
 DC Voltage + 18 Volts
 Continuous RF Input Power + 18 dBm
 Short Term RF Input Power 50 Milliwatts
 (1 Minute Max.)
 Maximum Peak Power 0.5 Watt
 (3 µsec Max.)

Typical Performance Data



Legend ——— + 25 °C - - - - + 85 °C ······ -55 °C

Linear S-Parameters

FREQ. MHz	S11		S21		S12		S22	
	Mag	Deg	Mag	Deg	Mag	Deg	Mag	Deg
10	.13	-115	5.08	-173	.10	10	.23	153
50	.08	-168	5.23	161	.10	- 6	.16	177
100	.06	-170	5.19	138	.10	- 18	.16	-171
200	.07	-123	5.07	93	.11	- 39	.18	-169
300	.15	-155	5.04	45	.11	- 66	.11	159
400	.22	97	4.82	- 16	.12	-108	.12	- 14



2707 Black Lake Place, Philadelphia, PA 19154

TEL 215-464-4000 •••• FAX 215-464-4001 3/14/03