

HA13492


Quad Solenoid Driver

Description

The HA13492, a monolithic power IC, is a driver for inductive loads especially for automotive application. Packaged in Single-in-Line 15 pin, contains four driving circuits of 0.8 A. Each driver has OCL* and independent OTSD** circuit to protect the IC from the short circuit of loads. Also include input open circuit protector and all of the failure condition can be reported by diagnostic circuit.

* OCL : Over current limiter

** OTSD : Over temperature shut down




Functions

- 0.8 A quad driver
- With clamp diodes
- With chip Enable
- With over voltage protector circuit
- With short circuit protector (OCL & OTSD)
- With diagnostic circuit
- With fail safe function under input open circuit condition

Features

- High sustaining voltage (45 V)
- Low saturation voltage
- Wide operating supply voltage range ($V_{CC} = 7$ to 25 V)
- Can stand for reverse voltage
- Low standby current (200 μ A max)
- With independent short circuit protector for each channel
- Compatible with TTL, LS-TTL and 5 V CMOS

Pin Arrangement



Ordering Information

Type No.	Package
HA13492	SP-15TA



Hitachi America, Ltd. • Hitachi Plaza • 2000 Sierra Point Pkwy. • Brisbane, CA 94005-1819 • (415) 589-8300


169

Truth Table

Enable	In	Out	Fault	Operating condition
L	X	H	H	Normal condition
H	H	L	H	
H	L	H	H	
H	H	H	L	Short circuit of load, OCL, OTSD, OVSD
H	L	L	L	Open circuit of load

Enable, in { H : High level ; 2.0 V
 L : Low level ; 0.8 V
 X : Don't care

Block Diagram



Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	Ratings	Units	Note
Supply voltage	V _{CC}	-13 to 45	V	1
Input voltage	V _{IN}	-0.6 to 7	V	
Output voltage	V _{CEX}	45	V	
Output current	I _O	1.5	A	2
Power dissipation	P _T	3.5	W	
Junction temperature	T _j	150	°C	
Operating junction temperature range	T _{jop}	-40 to +135	°C	
Storage temperature range	T _{stg}	-55 to +150	°C	
Package thermal resistance	θ _{j-c}	3	°C/W	3
	θ _{j-a}	60	°C/W	

The absolute maximum ratings are limiting values, to be applied individually, beyond which the device may be permanently damaged. Functional operation under any of these conditions is not guaranteed. Exposing a circuit to its absolute maximum rating for extended periods of time may affect the device's reliability.

Notes:

1. Recommended operating voltage

V_{CC} = 7 to 16 V (normal)
16 to 25 V (jump start)

2. Internally limited.
3. θ_{j-c}; Thermal resistance from junction to case
θ_{j-a}; Thermal resistance from junction to air



Hitachi America, Ltd. • Hitachi Plaza • 2000 Sierra Point Pkwy. • Brisbane, CA 94005-1819 • (415) 589-8300

171

HA13492

Electrical Characteristics ($T_a = 25^\circ\text{C}$, $V_{CC} = 12 \text{ V} \pm 10\%$)

Item	Symbol	Min	Typ	Max	Units	Test condition	Applicable pin	Note
Supply current	I _{CC0}	—	55	200	μA	Enable = 0.8 V	7	
	I _{CC}	—	80	100	mA	Enable = 2 V, $I_{out} = 0 \text{ to } 0.8 \text{ A} \times 4 \text{ CH}$		
Input	V _{IL}	—	—	0.8	V		9, 2, 6 10, 14	
	V _{IH}	2.0	—	—	V			
Low level current	I _{IL}	—10	—	40	μA	V _{IN} = 0 to 0.8 V (Enable = 2 V)	2, 6 10, 14	
		—10	—	40	μA	Enable = 0 to 0.8 V	9	
High level current	I _{IH}	10	35	60	μA	V _{IN} = 2.0 to 5.5 V (Enable = 2 V)	2, 6 10, 14	
		10	40	60	μA	Enable = 2.0 to 5.5 V	9	
		—5	—	10	μA	V _{IN} = 5.5 V (Enable = 0.8 V)	2, 6 10, 14	
Output	V _{CE(sat)}	—	0.08	0.15	V	$I_{out} = 0.1 \text{ A}$	3, 5, 11 13	
		—	0.30	0.40	V	$I_{out} = 0.5 \text{ A}$		
		—	0.60	0.75	V	$I_{out} = 0.8 \text{ A}$		
Leakage current	I _{CEX1}	—	0.5	5	mA	Enable = 2 V, V _{IN} = 0.8 V V _{CE} = 45 V		
	I _{CEX2}	200	400	600	μA	Enable = 2 V, V _{IN} = 0.8 V V _{CE} = 12 V		
	I _{CEX3}	—	—	100	μA	Enable = 0.8 V, V _{CE} = 45 V		
Sustaining voltage	V _{CE(sus)}	45	—	—	V		1	
Clamp diode	Forward voltage	V _F	—	1.3	V	$I_F = 1.0 \text{ A}$	3, 4, 5, 11 12, 13	2
		—	1.5	2.5	V	$I_F = 1.5 \text{ A}$		
Leakage current	I _R	—	—	100	μA	V _R = 50 V		
Fault out	Sink current	I _{OL}	30	—	125	μA	V _{Fault} = 1 to 5.5 V	1
	Low level voltage	V _{OL}	—	0.2	0.4	V	$I_{Fault} = 30 \mu\text{A}$	
	Leakage current	I _{LEAK}	—	—	2	μA	V _{Fault} = 1 to 5.5 V	



Electrical Characteristics ($T_a = 25^\circ\text{C}$, $V_{CC} = 12 \text{ V} \pm 10\%$) (cont)

Item	Symbol	Min	Typ	Max	Units	Test condition	Applicable pin	Note
Output error sense threshold voltage	V^+	—	—	7	V	Enable = 2 V, $V_{IN} = 2 \text{ V}$	3, 5, 11	3
	V^-	3	—	—	V	Enable = 2 V, $V_{IN} = 0.8 \text{ V}$	13	
Turn on and turn off delay	t_{PHL}	—	8	15	μs	$I_{out} = 0.5 \text{ A}$	2, 6, 10 14, 3, 5 11, 13	
	t_{PLH}	—	3	15	μs			
OVSD Starting voltage	V_{OVSD}	25.5	—	31	V		7	
Hysteresis	V_{HYS}	0.25	—	—	V			
OCL starting current	I_{OCL}	—	1.2	1.5	A		3, 5, 11	4
OTSD Starting temp	OTSD	145	—	—	$^\circ\text{C}$			13
Hysteresis	T_{HYS}	—	—	20	$^\circ\text{C}$			5

- Notes:
1. See figure 1
 2. See figure 2
 3. See figure 3
 4. See figure 4
 5. Design parameter only




Figure 1 Output Sustaining Voltage Test




Figure 2 Clamp Diode V_F Test




Figure 3 Output Error Sense Threshold Voltage Test




Figure 4 Over Current Limiter Test

HITACHI