


CM8V-T1A

Tuning Fork Crystal 32.768 kHz



DIMENSIONS



All dimensions in mm typical

Smallest SMT ceramic package
Ultra low profile: 0.60 mm height
SMD-package in Tape and Reel
Ind. and Ext. temperature ranges
High stability
Low aging
Low power consumption
High shock and vibration resistance

DESCRIPTION:

This SMD ceramic package has been specially designed for miniature telecom and portable applications. The Ultra Miniature Tuning Fork (UMTF) in this product is achieved by a special manufacturing process, this technology leads to improved electrical characteristics.

For pick-and-place equipment, the parts are available in 8 mm tape:

- 7" (178 mm) reel with 1'000 crystals
- 7" (178 mm) reel with 3'000 crystals
- 13" (330 mm) reel with 14'000 crystals

ELECTRICAL CHARACTERISTICS AT 25°C:

Nominal Frequency	¹⁾ F _L	32.768	kHz
Load capacitance	²⁾ C _L	7.0 / 9.0 / 12.5	pF
Frequency tolerance	³⁾ ΔF/F	+/-20	ppm
		+/-100	ppm
Series resistance max.	R _S	90	kΩ
Motional capacitance typ.	C ₁	3.5	fF
Static capacitance typ.	C ₀	1.0	pF
Drive level max.	P	0.5	μW
Insulation resistance min.	R _i	500	MΩ
Aging first year max.	ΔF/F	+/-3	ppm
Turnover temperature	T ₀	25 +/-5	°C
Frequency vs. temperature	ΔF/F ₀	-0.035 ppm/°C × (T - T ₀) ² +/-10%	ppm

- 1) Other frequencies on request.
- 2) Other load capacitances on request.
- 3) Tighter and wider frequency tolerances on request.

STANDARD FREQUENCIES:

Frequency kHz
32.768
Other frequencies on request

**ENVIRONMENTAL
CHARACTERISTICS:**

		Conditions	Max. Dev.
Storage temp. range		-55 to +125°C	
TA Operating temperature range		-40 to +85°C	
Shock resistance	ΔF/F	5000 g, 0.3 ms, ½ sine	+/-5 ppm
Vibration resistance	ΔF/F	20 g / 10–2000 Hz	+/-5 ppm

**TERMINATIONS AND
PROCESSING:**

Type	Termination	Processing
CM8V-T1A	For SMD mounting Au plated pads	Reflow soldering 260°C / 20 s max.

**PRODUCT DESCRIPTION AND
ORDERING INFORMATION:**

CM8V-T1A	<u>32.768kHz</u>	<u>12.5pF</u>	<u>+/-20ppm</u>	<u>TA</u>	<u>QC</u>
Frequency F_L	_____				
C_L Load Capacitance	_____				
7.0 pF					
9.0 pF					
12.5 pF					
Frequency tolerance	_____				
+/- 20 ppm					
+/- 100 ppm					
	Temperature Range				_____
	TA = -40 to 85°C (Standard)				
Optional: if not defined, 'Standard' will apply	Qualification				_____
	QC = Commercial (Standard)				
A unique part number will be generated for each product specification, i.e:					
20xxxx-MC01	1'000 pcs (in 8mm tape on 7" reel)				
20xxxx-MC03	3'000 pcs (in 8mm tape on 7" reel)				
20xxxx-PC14	14'000 pcs (in 8mm tape on 13" reel)				
Please contact us.					

All specifications subject to change without notice.



Micro Crystal AG
Mühlestrasse 14
CH-2540 Grenchen
Switzerland

Tel. +41 32 655 82 82
Fax +41 32 655 82 83
sales@microcrystal.com
www.microcrystal.com