


# 1,800 V Rectifiers

## 250 mA Forward Current

## 30 ns - 50 ns Recovery Time


**MD60FF18**  
**MD60F18**




### ELECTRICAL CHARACTERISTICS AND MAXIMUM RATINGS

Part Number	Working Reverse Voltage (V <sub>rw</sub> )	Average Rectified Current (I <sub>o</sub> )		Reverse Current @ V <sub>rw</sub> (I <sub>r</sub> )		Forward Voltage (V <sub>f</sub> )		1 Cycle Surge Current I <sub>p</sub> =8.3ms (I <sub>fsm</sub> )	Repetitive Surge Current (I <sub>frm</sub> )	Reverse Recovery Time (3) (T <sub>rr</sub> )	Thermal Impd. θ <sub>J-L</sub>	Junction Cap. @50VDC @1kHz (C <sub>j</sub> )	Markings
		55°C(1)	100°C(2)	25°C	100°C	25°C	25°C						
		Volts	Amps	Amps	µA	µA	Volts						
MD60FF18	1800	0.25	0.15	1.0	25	4.0	0.25	10	2	30	13	20	FF18
MD60F18	1800	0.25	0.15	1.0	25	4.0	0.25	10	2	50	13	20	F18

(1) TC=55°C (2)TC=100°C (3)I<sub>f</sub>=0.5A, I<sub>r</sub>=1.0A, I<sub>rr</sub>=0.25A \*Op. Temp.= -65°C to +175°C Stg. Temp.= -65°C to +200°C



Plating:  
50µin silver over 50µin nickel.



Dimensions: In. (mm) • All temperatures are ambient unless otherwise noted. • Data subject to change without notice.



**VOLTAGE MULTIPLIERS INC.**  
8711 W. Roosevelt Ave.  
Visalia, CA 93291

TEL 559-651-1402  
FAX 559-651-0740  
www.voltagemultipliers.com