


Features

- Ideally Suited for Automatic Insertion
- For Switching and AF Amplifier Applications
- Ultra-Small Surface Mount Package

Mechanical Data

- Case: SOT-363, Molded Plastic
- Case material - UL Flammability Rating Classification 94V - 0
- Moisture sensitivity: Level 1 per J-STD-020A
- Terminals: Solderable per MIL-STD-202, Method 208
- Terminal Connections: See Diagram
- Marking: K1F (See Page 2)
- Weight: 0.006 grams
- Ordering & Date Code Information: See Page 2



SOT-363		
Dim	Min	Max
A	0.10	0.30
B	1.15	1.35
C	2.00	2.20
D	0.65 Nominal	
F	0.30	0.40
H	1.80	2.20
J	—	0.10
K	0.90	1.00
L	0.25	0.40
M	0.10	0.25
α	°8	
All Dimensions in mm		

Maximum Ratings @ T_A = 25°C unless otherwise specified

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	V _{CB0}	50	V
Collector-Emitter Voltage	V _{CE0}	45	V
Emitter-Base Voltage	V _{EB0}	5.0	V
Collector Current	I _C	100	mA
Peak Collector Current	I _{CM}	200	mA
Peak Base Current	I _{BM}	200	mA
Power Dissipation (Note 1)	P _d	200	mW
Thermal Resistance, Junction to Ambient (Note 1)	R _{θJA}	500	°C/W
Operating and Storage Temperature Range	T _J , T _{STG}	-55 to +125	°C

Notes: 1. Device mounted on FR-4 PCB, 1 inch x 0.85 inch; pad layout as shown on Diodes Inc. suggested pad layout document AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.

Electrical Characteristics @ T_A = 25°C unless otherwise specified


Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
DC Current Gain (Note 2)	h _{FE}	200	—	450	—	V _{CE} = 5.0V, I _C = 2.0mA
Collector-Emitter Saturation Voltage (Note 2)	V _{CE(SAT)}	—	—	100 400	mV	I _C = 10mA, I _B = 0.5mA I _C = 100mA, I _B = 5.0mA
Base-Emitter Saturation Voltage (Note 2)	V _{BE(SAT)}	—	755	—	mV	I _C = 10mA, I _B = 0.5mA
Base-Emitter Voltage (Note 2)	V _{BE}	580	665	700	mV	V _{CE} = 5.0V, I _C = 2.0mA
Collector Cutoff Current (Note 2)	I _{CBO} I _{CBO}	—	—	15 5.0	nA μA	V _{CB} = 30V, I _E = 0 V _{CB} = 30V, T _J = 125°C
Emitter Cutoff Current (Note 2)	I _{EBO}	—	—	100	nA	V _{EB} = 5.0V, I _C = 0
Gain Bandwidth Product	f _T	100	—	—	MHz	V _{CE} = 5.0V, I _C = 10mA, f = 100MHz
Collector-Base Capacitance	C _{CB0}	—	—	1.5	pF	V _{CB} = 10V, f = 1.0MHz
Emitter-Base Capacitance	C _{EB0}	—	11	—	pF	V _{EB} = 0.5V, f = 1.0MHz

Ordering Information (Note 3)

Device	Packaging	Shipping
BC847BS-7	SOT-363	3000/Tape & Reel

- Notes: 2. Short duration pulse test used to minimize self-heating effect.
3. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information



K1F = Product Type Marking Code
YM = Date Code Marking
Y = Year ex: N = 2002
M = Month ex: 9 = September

Date Code Key

Year	1998	1999	2000	2001	2002	2003	2004
Code	J	K	L	M	N	P	R

Month	Jan	Feb	March	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D




Fig. 1, Power Derating Curve




Fig. 2, DC Current Gain vs. Collector Current




Fig. 3, Collector Saturation Voltage vs. Collector Current




Fig. 4, Gain Bandwidth Product vs. Collector Current

Notes: 1. Device mounted on FR4 printed circuit board.