



PRODUCT SPECIFICATION

Model No.: CSDS-2D107VMB

Descriptions:
<ul style="list-style-type: none"> ■ 2.3 Inch Single Digit Display ■ Common Cathode ■ Emitting Color: Rich Color(Red,Green,Blue) ■ Black Face ■ White Segment



CUSTOMER APPROVED SIGNATURES	APPROVED BY	CHECKED BY	PREPARED BY

CHINA SEMICONDUCTOR CORPORATION
Address:2FL. NO.909,Chung-Cheng Road,
Chung-Ho City Taipei Hsien,Taiwan.

Tel:886-2-2223-9696
Fax:886-2-2223-9377

OPTO PLUS TECHNOLOGIES CO.,LTD
Address:696 Shun jiang Rd.,Shaoxing,
ZheJiang,China

Tel:86-0575-88623888
Fax:86-0575-88623112



Model No.: CSDS-2D107VMB


Features -

1. 2.3 inch (56.80mm) digit height.
2. Case mold type.
3. RoHS compliant.
4. Low power consumption.
5. Standard: black face, white segment.
6. Easy mounting on P.C. board or socket.

Device Selection Guide -

Model No.	Chip		Description
	Material	Emitting Color	
CSDS-2D107VMB	AlGaInP	Super Bright Orange	Common Cathode
	InGaN	Super Bright Pure Green	
	InGaN	Super Bright Blue	

Mechanical Dimensions -




Notes:

1. All pins are $\phi 0.60 [0.024]$
2. Dimension in millimeter [inch], tolerance is $\pm 0.25 [0.010]$ and angle is $\pm 1^\circ$ unless otherwise noted.
3. Bending \leq Length * 1%.



Model No.: **CSDS-2D107VMB**

Internal Circuit Diagrams -





Model No.: CSDS-2D107VMB

■ **Absolute Maximum Rating -**

Super Bright Orange		(Ta=25°C)	
Parameter	Symbol	Rating	Unit
Power Dissipation Per Dice	P _{AD}	70	mW
Derating Liner from 25°C per Dice	-	0.33	mA/°C
Continuous Forward Current Per Dice	I _{AF}	25	mA
Peak Current Per Dice(duty cycle 1/10,1KHz)	I _{PF}	90	mA
Reverse Voltage Per Dice	VR	5	V
Operating Temp.	Topr	-35 ~ +85	°C
Storage Temp.	Tstg	-35 ~ +85	°C

Super Bright Pure Green		(Ta=25°C)	
Parameter	Symbol	Rating	Unit
Power Dissipation Per Dice	P _{AD}	114	mW
Derating Liner from 25°C per Dice	-	0.4	mA/°C
Continuous Forward Current Per Dice	I _{AF}	30	mA
Peak Current Per Dice(duty cycle 1/10,1KHz)	I _{PF}	100	mA
Reverse Voltage Per Dice	VR	5	V
Electrostatic discharge(HBM)	ESD	1	KV
Operating Temp.	Topr	-35 ~ +85	°C
Storage Temp.	Tstg	-35 ~ +85	°C

Super Bright Blue		(Ta=25°C)	
Parameter	Symbol	Rating	Unit
Power Dissipation Per Dice	P _{AD}	114	mW
Derating Liner from 25°C per Dice	-	0.4	mA/°C
Continuous Forward Current Per Dice	I _{AF}	30	mA
Peak Current Per Dice(duty cycle 1/10,1KHz)	I _{PF}	100	mA
Reverse Voltage Per Dice	VR	5	V
Electrostatic discharge(HBM)	ESD	1	KV
Operating Temp.	Topr	-35 ~ +85	°C
Storage Temp.	Tstg	-35 ~ +85	°C



Model No.: CSDS-2D107VMB

■ Electro-optical Characteristics -

(Ta=25°C)

Super Bright Orange						
Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Forward Voltage Per Segment(DP)	V _F	-	8.0(2.0)	11.2(2.8)	V	I _F =20mA
Luminous Intensity Per Segment	I _v	94	234	-	mcd	I _F =10mA
Peak Emission Wavelength	λ _P	-	632	-	nm	I _F =20mA
Dominant Wavelength	λ _d	-	624	-	nm	I _F =20mA
Spectrum Radiation Bandwidth	Δ λ	-	20	-	nm	I _F =20mA
Reverse Current(DP)	I _R	-	-	100	μA	V _R =20(5)V
Luminous Intensity Matching Ratio	I _{V-m}	-	-	2:1	-	I _F =10mA

Super Bright Pure Green						
Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Forward Voltage Per Segment(DP)	V _F	-	12.8(3.2)	15.2(3.8)	V	I _F =20mA
Luminous Intensity Per Segment	I _v	150	375	-	mcd	I _F =10mA
Dominant Wavelength	λ _d	-	525	-	nm	I _F =20mA
Spectrum Radiation Bandwidth	Δ λ	-	30	-	nm	I _F =20mA
Reverse Current(DP)	I _R	-	-	50	μA	V _R =20(5)V
Luminous Intensity Matching Ratio	I _{V-m}	-	-	2:1	-	I _F =10mA

Super Bright Blue						
Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Forward Voltage Per Segment(DP)	V _F	-	12.8(3.2)	15.2(3.8)	V	I _F =20mA
Luminous Intensity Per Segment	I _v	58	146	-	mcd	I _F =10mA
Peak Emission Wavelength	λ _P	-	468	-	nm	I _F =20mA
Dominant Wavelength	λ _d	-	470	-	nm	I _F =20mA
Spectrum Radiation Bandwidth	Δ λ	-	30	-	nm	I _F =20mA
Reverse Current(DP)	I _R	-	-	50	μA	V _R =20(5)V
Luminous Intensity Matching Ratio	I _{V-m}	-	-	2:1	-	I _F =10mA



Model No.: CSDS-2D107VMB

Typical Electrical / Optical Characteristics Curves -Super Bright Orange

(Ta = 25°C Unless Otherwise Noted)




Fig 1. Forward Current vs. Forward Voltage




Fig 2. Relative Intensity vs. Forward Current




Fig 3. Forward Voltage vs. Temperature




Fig 4. Relative Intensity vs. Temperature




Fig 5. Relative Intensity vs. Wavelength



Model No.: **CSDS-2D107VMB**

● **Super Bright Pure Green**

(Ta = 25°C Unless Otherwise Noted)




Fig 1. Forward Current vs. Forward Voltage




Fig 2. Relative Intensity vs. Forward Current




Fig 3. Forward Voltage vs. Temperature




Fig 4. Relative Intensity vs. Temperature




Fig 5. Relative Intensity vs. Wavelength



Model No.: **CSDS-2D107VMB**

● **Super Bright Blue**

(Ta = 25°C Unless Otherwise Noted)




Fig 1. Forward Current vs. Forward Voltage




Fig 2. Relative Intensity vs. Forward Current




Fig 3. Forward Voltage vs. Temperature




Fig 4. Relative Intensity vs. Temperature




Fig 5. Relative Intensity vs. Wavelength




Model No.: CSDS-2D107VMB

■ Precautions For Use -

1. Recommended Soldering conditions

Wave Soldering




2. Soldering Iron

Basic SPEC. is ≤ 5 sec. When 260°C . If temperature is higher, time should be shorter ($+10^{\circ}\text{C} \rightarrow -1$ sec.). Power dissipation of iron should be smaller than 15W, and temperature should be controllable. Surface temperature of the device should be under 230°C .




Model No.: CSDS-2D107VMB

■ Package Dimensions



12 Pcs Per PE.foam
PE.foam Size:
L295xW195xH15mm



8 PE.foam Per Box
Q'TY :96 PCS
Box Size:
L300*W205*H240mm

Note: The specifications are subject to change without notice. Please contact us for updated information.