



TC206B

Features:

- Surface mount pick & place
- High performance/cost ratio

Specifications		Symbol	TC-206B		Remarks
Frequency range		f	32.768kHz	32kHz ~ 200 kHz	
Frequency tolerance, Ta=25°C		f/f	±10ppm ~ ±100ppm		Others are offered
Load capacitance		C _L	12.5pF (Std.)	6pF ~ 12.5pF (Std.)	Please specify
Temp. coefficient		A	-0.035 ± 0,01ppm/°C ²		Max
Temperature range	Storage temperature	T _{STG}	-40°C ~ +85°C		Max (25°C±5°C)
	Operating temperature	T _{OPR}	-10°C - +60°C ~ -40°C - +85°C		Others are offered
Drive level	Maximum drive level	M _{DL}	1μW		Max
	Recommended drive level	R _{DL}	-		
Series resistance		R ₁	40k Ohm max		As per table (25°C ±3°C)
Shunt capacitance		C ₀	1.45pF	1.3pF	Typ
Insulation resistance		I _R	500M Ohm		Min
Aging		f _A	±5ppm/Year		Max

Resistance of series resonance (ESR)						
Frequency	Mode	Ohm max		Frequency	Mode	Ohm max
32kHz ≤ f < 40kHz	Fundamental	40k		60kHz ≤ f < 70kHz	Fundamental	25k
40kHz ≤ f < 60kHz	Fundamental	30k		70kHz ≤ f < 200kHz	Fundamental	22k

Drawing

TC206B

Do not solder can, please ask for processing guideline!

Recommended soldering pattern

Dimensions in mm

Order key						
Part	Frequency	Package	Frequency tolerance	Temperature range	Load capacitance	Option
Q	- 32.768000k	- TC206B	- 50	- B	- 12.5	- X
Q=Quartz	k=kHz	TC206B	±ppm (25°C)	A= 0°C ~ +70°C B= -10°C ~ +60°C C= -10°C ~ +70°C D= -20°C ~ +70°C E= -40°C ~ +85°C H= -20°C ~ +80°C I = -10°C ~ +50°C	pF SR=series	X=Special options