


# 2SC4981

(TP7S8)

## 7A NPN

### OUTLINE DIMENSIONS



### RATINGS


#### Absolute Maximum Ratings

Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T <sub>stg</sub>		-55 ~ 150	
Junction Temperature	T <sub>j</sub>		150	
Collector to Base Voltage	V <sub>CB0</sub>		100	V
Collector to Emitter Voltage	V <sub>CEO</sub>		80	V
Emitter to Base Voltage	V <sub>EBO</sub>		7	V
Collector Current DC	I <sub>C</sub>		7	A
Collector Current Peak	I <sub>CP</sub>		14	A
Base Current DC	I <sub>B</sub>		1.5	A
Base Current Peak	I <sub>BP</sub>		2	A
Total Transistor Dissipation	P <sub>T</sub>	T <sub>C</sub> = 25	25	W
Dielectric Strength	V <sub>dis</sub>	Terminal to case, AC 1 minute	2	kV
Mounting Torque	TOR	(Recommended torque : 0.3N·m)	0.5	N·m


#### Electrical Characteristics (T<sub>c</sub>=25 )

Item	Symbol	Conditions	Ratings	Unit
Collector to Emitter Sustaining Voltage	V <sub>CEO(sus)</sub>	I <sub>C</sub> = 0.1A	Min 80	V
Collector Cutoff Current	I <sub>CBO</sub>	At rated Voltage	Max 0.1	mA
	I <sub>CEO</sub>		Max 0.1	
Emitter Cutoff Current	I <sub>EBO</sub>	At rated Voltage	Max 0.1	mA
DC Current Gain	h <sub>FE</sub>	V <sub>CE</sub> = 2V, I <sub>C</sub> = 3.5A	Min 70	
Collector to Emitter Saturation Voltage	V <sub>CE(sat)</sub>	I <sub>C</sub> = 3.5A	Max 0.3	V
Base to Emitter Saturation Voltage	V <sub>BE(sat)</sub>	I <sub>B</sub> = 0.2A	Max 1.2	V
Thermal Resistance	θ <sub>JC</sub>	Junction to case	Max 5	/W
Transition Frequency	f <sub>T</sub>	V <sub>CE</sub> = 10V, I <sub>C</sub> = 0.7A	TYP 50	MHz
Turn on Time	t <sub>on</sub>	I <sub>C</sub> = 3.5A I <sub>B1</sub> = 0.35A, I <sub>B2</sub> = 0.35A R <sub>L</sub> = 8 Ω, V <sub>BB2</sub> = 4V	Max 0.3	μs
Storage Time	t <sub>s</sub>		Max 1.5	
Fall Time	t <sub>f</sub>		Max 0.2	

2SC4981  $h_{FE} - I_C$




## 2SC4981 Saturation Voltage




# 2SC4981


## Switching Time - $I_C$




## 2SC4981 Switching Time - Tc



2SC4981 Transient Thermal Impedance



# 2SC4981 Forward Bias SOA



## 2SC4981 Collector Current Derating

