

PX1385

Electrical data:

Connection	connector
Rated operational voltage DC	24 V
Rated insulation voltage (Ui)	75 DC
Electrical type	DC
No-load supply current I _o at I _e	10 mA
Supply voltage ripple	10 %
Switching element function	0...10 V
Supply voltage max. (U _b)	26,4 V
Supply voltage min. (U _b)	21,6 V
Output voltage s _l max	10 V
Output voltage s _l min	0 V
Cutoff frequency (-3dB output amplitude)	500 Hz
Load resistance min (R _L)	2000 Ohm
Output voltage at se	5 V
Load resistance min (R _L)	2000 Ohm
Temperature compensation	yes
UTemp typ at 25 °C	3.3 V
Linear range max (s _l)	5 mm
Linear range min (s _l)	1 mm
Non-linearity	±120 µm
Output signal	0...10 V


General data:

Supply voltage indicator	no
Degree of protection IP	IP 67
Recommended connector	BKS-_19/BKS-_20
Polarity reversal resistant	yes
Protected against reversal	no

Mechanical data:

Midpoint of linear range (se)	3 mm
Connection type	M12x1-S04
Mounting	flush mountable
Surface treatment	nickel plated
Ambient temperature max (T _a)	70 °C
Ambient temperature min (T _a)	-10 °C
Sensing face material	PBTP
Housing material	CuZn
Repeatability	3 %
Working area max (s _a)	5 mm
Working area min (s _a)	1 mm
Time delay before available max	1 ms
Measurement velocity	40 m/s
Opt. working temperature max.	50 °C
Opt. working temperature min.	10 °C
Temperature coefficient max.	4,0 µm/K
Temperature coefficient min.	0,0 µm/K
Temperature coefficient typ.	-1,0 µm/K
Temp. drift typ.	-9 mV/K
Repeat accuracy	±8,0 µm
Adjustment indicator	yes
Working range	1...5 mm

Wiring:



Pinout:

