


STANDARD TRIACS

FEATURES

- $I_{T(RMS)} = 4A$
- $V_{DRM} = 400V$ to $800V$
- $I_{GT} \leq 25mA$

DESCRIPTION

The Z0410xE/F series of triacs uses a high performance TOP GLASS PNP technology. These parts are intended for general purpose switching and phase control applications.



ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value	Unit
$I_{T(RMS)}$	RMS on-state current (360° conduction angle)	Z0410xE/F $T_c = 75^\circ C$	4	A
		Z0410xF $T_a = 25^\circ C$	0.95	
I_{TSM}	Non repetitive surge peak on-state current (T_j initial = $25^\circ C$)	$t_p = 8.3$ ms	22	A
		$t_p = 10$ ms	20	
I^2t	I^2t Value for fusing	$t_p = 10$ ms	2	A^2s
di/dt	Critical rate of rise of on-state current $I_G = 50$ mA $di_G/dt = 0.1$ A/ μs .	Repetitive F = 50 Hz	10	A/ μs
		Non Repetitive	50	
T_{stg} T_j	Storage and operating junction temperature range		- 40, + 150 - 40, + 125	$^\circ C$
TI	Maximum lead temperature for soldering during 10s at 4.5mm from case		260	$^\circ C$

Symbol	Parameter	Voltage				Unit
		D	M	S	N	
V_{DRM} V_{RRM}	Repetitive peak off-state voltage $T_j = 125^\circ C$	400	600	700	800	V

Z0410xE/F

THERMAL RESISTANCES

Symbol	Parameter		Value	Unit
Rth(j-a)	Junction to ambient	Z0410xE	80	°C/W
		Z0410xF	100	
Rth(j-c)	Junction to case for D.C		10	°C/W
Rth(j-c)	Junction to case for A.C 360° conduction angle (F=50Hz)		7.5	°C/W

GATE CHARACTERISTICS (maximum values)

$P_{G(AV)} = 0.2 \text{ W}$ $P_{GM} = 3 \text{ W}$ ($t_p = 20 \mu\text{s}$) $I_{GM} = 1.2 \text{ A}$ ($t_p = 20 \mu\text{s}$)

ELECTRICAL CHARACTERISTICS

Symbol	Test Conditions	Quadrant		Sensitivity		Unit
					10	
I_{GT}	$V_D = 12\text{V (DC)}$ $R_L = 33\Omega$ $T_j = 25^\circ\text{C}$	I-II-III-IV	MAX		25	mA
V_{GT}	$V_D = 12\text{V (DC)}$ $R_L = 33\Omega$ $T_j = 25^\circ\text{C}$	I-II-III-IV	MAX		1.5	V
V_{GD}	$V_D = V_{DRM}$ $R_L = 3.3\text{k}\Omega$ $T_j = 125^\circ\text{C}$	I-II-III-IV	MIN		0.2	V
tgt	$V_D = V_{DRM}$ $I_G = 40\text{mA}$ $I_T = 5.5\text{A}$ $di_G/dt = 0.5\text{A}/\mu\text{s}$ $T_j = 25^\circ\text{C}$	I-II-III-IV	TYP		2	μs
I_H^*	$I_T = 50 \text{ mA}$ Gate open $T_j = 25^\circ\text{C}$		MAX		25	mA
I_L	$I_G = 1.2 I_{GT}$ $T_j = 25^\circ\text{C}$	I-III-IV	TYP		25	mA
		II	TYP		50	
V_{TM}^*	$I_{TM} = 5.5\text{A}$ $t_p = 380\mu\text{s}$ $T_j = 25^\circ\text{C}$		MAX		2	V
I_{DRM} I_{RRM}	$V_D = V_{DRM}$ $V_R = V_{RRM}$ $T_j = 25^\circ\text{C}$		MAX		5	μA
			MAX		200	
dV/dt *	$V_D = 67\% V_{DRM}$ Gate open $T_j = 110^\circ\text{C}$		MIN		200	V/ μs
			TYP		400	
(dV/dt)c *	(di/dt)c = 1.8 A/ms $T_j = 110^\circ\text{C}$		MIN		5	V/ μs

* For either polarity of electrode A_2 voltage with reference to electrode A_1

ORDERING INFORMATION




Fig.1 : Maximum RMS power dissipation versus RMS on-state current.




Fig.3 : Maximum RMS power dissipation versus RMS on-state current.




Fig.5 : RMS on-state current versus case temperature (TO202-1).




Fig.2 : Correlation between maximum RMS power dissipation and maximum allowable temperature (Tamb and Tcase) for different thermal resistances heatsink + contact (TO202-1).




Fig.4 : Correlation between maximum RMS power dissipation and maximum allowable temperature (Tamb and Tcase) (TO202-2).




Fig.6 : RMS on-state current versus case temperature (TO202-2).




Fig.6 : Relative variation of thermal impedance versus pulse duration (TO202-1).




Fig.7 : Relative variation of thermal impedance junction to ambient versus pulse duration (TO202-2).




Fig.9 : Relative variation of gate trigger current and holding current versus junction temperature.




Fig.10 : Non repetitive surge peak on-state current versus number of cycles.




Fig.11 : Non repetitive surge peak on-state current for a sinusoidal pulse with width : $tp \leq 10ms$, and corresponding value of I^2t .





Fig.12 : On-state characteristics (maximum values).



PACKAGE MECHANICAL DATA
TO202-1 (Plastic)

REF.	DIMENSIONS					
	Millimeters			Inches		
	Typ.	Min.	Max.	Typ.	Min.	Max.
A			10.1			0.398
B	13.7			0.540		
C	7.3			0.287		
D	10.5			0.413		
F			1.5			0.059
G	3.2			0.126		
H	0.51			0.020		
I		3.16	3.20		0.124	0.126
J	1.5			0.059		
M	4.5			0.177		
N			5.3			0.209
N1	2.54			0.100		
O			1.4			0.055
P			0.7			0.028

Marking : type number
Weight : 1.4 g

Z0410xE/F

PACKAGE MECHANICAL DATA TO202-2 (Plastic)

REF.	DIMENSIONS					
	Millimeters			Inches		
	Typ.	Min.	Max.	Typ.	Min.	Max.
A			10.1			0.398
B	1.2			0.047		
C	7.3			0.287		
D	10.5			0.413		
E	7.4			0.290		
F			1.5			0.059
H	0.51			0.020		
J	1.5			0.059		
M	4.5			0.177		
N			5.3			0.209
N1	2.54			0.100		
O			1.4			0.055
P			0.7			0.028

Marking : type number
Weight : 1.0 g

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1995 SGS-THOMSON Microelectronics - All rights reserved.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.