

www.DataSheet4U.com

2SK796, 2SK796A

Silicon N-channel Power F-MOS FET

■ Features

- Low ON resistance $R_{DS(on)}$: $R_{DS(on)} = 3.0\Omega$ (typ.)
- High switching rate : $t_f = 40\text{ns}$ (typ.)
- No secondary breakdown
- High breakdown voltage, large power

■ Application

- No contact relay
- Solenoid drive
- Motor drive
- Control equipment
- Switching power source

■ Absolute Maximum Ratings (Tc=25°C)

Item	Symbol	Value	Unit
Drain-source voltage	2SK796	800	V
	2SK796A	900	
Gate-source voltage	V_{GSS}	± 20	V
Drain current	DC	3	A
	Peak to peak value	6	
Power dissipation	Tc = 25°C	90	W
	Ta = 25°C	3.0	
Channel temperature	Tch	150	°C
Storage temperature	Tstg	-55 ~ +150	°C

■ Electrical Characteristics (Tc=25°C)

Item	Symbol	Condition	min.	typ.	max.	Unit
Drain current	I_{DSS}	$V_{DS} = 640\text{V}$, $V_{GS} = 0$			0.1	mA
Gate-source current	I_{GSS}	$V_{GS} = \pm 20\text{V}$, $V_{DS} = 0$			± 1	μA
Drain-source voltage	V_{DSS}	$I_D = 1\text{mA}$, $V_{GS} = 0$	800			V
			900			
Gate threshold voltage	V_{th}	$V_{DS} = 25\text{V}$, $I_D = 1\text{mA}$	1		5	V
Drain-source ON resistance	$R_{DS(on)}$	$V_{GS} = 10\text{V}$, $I_D = 2\text{A}$		3.5	5.0	Ω
Forward transfer admittance	$ Y_{fs} $	$V_{DS} = 25\text{V}$, $I_D = 2\text{A}$	0.7	1.7		S
Input capacitance	C_{iss}	$V_{DS} = 20\text{V}$, $V_{GS} = 0$, $f = 1\text{MHz}$		600		pF
Output capacitance	C_{oss}				110	pF
Reverse transfer capacitance	C_{rss}				50	pF
Turn-on time	t_{on}				55	ns
Fall time	t_f	$V_{GS} = 10\text{V}$, $I_D = 2\text{A}$		40		ns
Delay time	t_d (off)	$V_{DD} = 200\text{V}$, $R_L = 100\Omega$		110		ns

■ Package Dimensions

