

Schottky Barrier Rectifiers

Using the Schottky Barrier principle with a Molybdenum barrier metal. These state-of-the-art geometry features epitaxial construction with oxide passivation and metal overlay contact. Ideally suited for low voltage, high frequency rectification, or as free wheeling and polarity protection diodes.

- ┆ Low Forward Voltage.
- ┆ Low Switching noise.
- ┆ High Current Capacity
- ┆ Guarantee Reverse Avalanche.
- ┆ Guard-Ring for Stress Protection.
- ┆ Low Power Loss & High efficiency.
- ┆ 150 ϕ Operating Junction Temperature
- ┆ Low Stored Charge Majority Carrier Conduction.
- ┆ Plastic Material used Carries Underwriters Laboratory Flammability Classification 94V-O

SCHOTTKY BARRIER RECTIFIERS


**30 AMPERES
30-60 VOLTS**



TO-3P

MAXIMUM RATINGS


Characteristic	Symbol	S30D						Unit
		30CE	35CE	40CE	45CE	50CE	60CE	
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	30	35	40	45	50	60	V
RMS Reverse Voltage	$V_{R(RMS)}$	21	25	28	32	35	42	V
Average Rectifier Forward Current Total Device (Rated V_R), $T_C=100\phi$	$I_{F(AV)}$	15 30						A
Peak Repetitive Forward Current (Rate V_R , Square Wave, 20kHz)	I_{FM}	30						A
Non-Repetitive Peak Surge Current (Surge applied at rate load conditions halfwave, single phase, 60Hz)	I_{FSM}	300						A
Operating and Storage Junction Temperature Range	T_J, T_{STG}	-65 to +125						ϕ



DIM	MILLIMETERS	
	MIN	MAX
A	20.63	22.38
B	15.38	16.20
C	1.90	2.70
D	5.10	6.10
E	14.81	15.22
F	11.72	12.84
G	4.20	4.50
H	1.82	2.46
I	2.92	3.23
J	0.89	1.53
K	5.26	5.66
L	18.50	21.50
M	4.68	5.36
N	2.40	2.80
O	3.25	3.65
P	0.55	0.70

ELECTRIAL CHARACTERISTICS

Characteristic	Symbol	S30D						Unit	
		30CE	35CE	40CE	45CE	50CE	60CE		
Maximum Instantaneous Forward Voltage ($I_F=15$ Amp $T_C=25\phi$) ($I_F=15$ Amp $T_C=100\phi$)	V_F	0.57 0.46						0.65 0.55	V
Maximum Instantaneous Reverse Current (Rated DC Voltage, $T_C=25\phi$) (Rated DC Voltage, $T_C=125\phi$)	I_R	1.0 30							mA



Common cathode
Suffix "C"

S30D30CE Thru S30D60CE

FIG-1 FORWARD CURRENT DERATING CURVE




FIG-2 TYPICAL FORWARD CHARACTERISTICS




FIG-3 TYPICAL REVERSE CHARACTERISTICS




FIG-4 TYPICAL JUNCTION CAPACITANCE




FIG-5 PEAK FORWARD SURGE CURRENT

