



**MOTOROLA**

Order this document by MC33272A/D

## MC33272A MC33274A

# Single Supply, High Slew Rate Low Input Offset Voltage, Bipolar Operational Amplifiers

The MC33272/74 series of monolithic operational amplifiers are quality fabricated with innovative Bipolar design concepts. This dual and quad operational amplifier series incorporates Bipolar inputs along with a patented Zip-R-Trim element for input offset voltage reduction. The MC33272/74 series of operational amplifiers exhibits low input offset voltage and high gain bandwidth product. Dual-doublet frequency compensation is used to increase the slew rate while maintaining low input noise characteristics. Its all NPN output stage exhibits no deadband crossover distortion, large output voltage swing, and an excellent phase and gain margin. It also provides a low open loop high frequency output impedance with symmetrical source and sink AC frequency performance.

The MC33272/74 series is specified over  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$  and are available in plastic DIP and SOIC surface mount packages.


- Input Offset Voltage Trimmed to 100  $\mu\text{V}$  (Typ)
- Low Input Bias Current: 300 nA
- Low Input Offset Current: 3.0 nA
- High Input Resistance: 16 M $\Omega$
- Low Noise: 18 nV/ $\sqrt{\text{Hz}}$  @ 1.0 kHz
- High Gain Bandwidth Product: 24 MHz @ 100 kHz
- High Slew Rate: 10 V/ $\mu\text{s}$
- Power Bandwidth: 160 kHz
- Excellent Frequency Stability
- Unity Gain Stable: w/Capacitance Loads to 500 pF
- Large Output Voltage Swing: +14.1 V / -14.6 V
- Low Total Harmonic Distortion: 0.003%
- Power Supply Drain Current: 2.15 mA per Amplifier
- Single or Split Supply Operation: +3.0 V to +36 V or  $\pm 1.5$  V to  $\pm 18$  V
- ESD Diodes Provide Added Protection to the Inputs

### ORDERING INFORMATION

Op Amp Function	Device	Operating Temperature Range	Package
Dual	MC33272AD	$T_A = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$	SO-8
	MC33272AP		Plastic DIP
Quad	MC33274AD		SO-14
	MC33274AP		Plastic DIP

### HIGH PERFORMANCE OPERATIONAL AMPLIFIERS



#### SEMICONDUCTOR TECHNICAL DATA



P SUFFIX  
PLASTIC PACKAGE  
CASE 626

D SUFFIX  
PLASTIC PACKAGE  
CASE 751  
(SO-8)


### PIN CONNECTIONS



P SUFFIX  
PLASTIC PACKAGE  
CASE 646

D SUFFIX  
PLASTIC PACKAGE  
CASE 751A  
(SO-14)

### PIN CONNECTIONS



# MC33272A MC33274A

## MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Supply Voltage	V <sub>CC</sub> to V <sub>EE</sub>	+36	V
Input Differential Voltage Range	V <sub>IDR</sub>	(Note 1)	V
Input Voltage Range	V <sub>IR</sub>	(Note 1)	V
Output Short Circuit Duration (Note 2)	t <sub>SC</sub>	Indefinite	sec
Maximum Junction Temperature	T <sub>J</sub>	+150	°C
Storage Temperature	T <sub>stg</sub>	-60 to +150	°C
Maximum Power Dissipation	P <sub>D</sub>	(Note 2)	mW

**NOTES:** 1. Either or both input voltages should not exceed V<sub>CC</sub> or V<sub>EE</sub>.

2. Power dissipation must be considered to ensure maximum junction temperature (T<sub>J</sub>) is not exceeded (see Figure 2).

## DC ELECTRICAL CHARACTERISTICS (V<sub>CC</sub> = +15 V, V<sub>EE</sub> = -15 V, T<sub>A</sub> = 25°C, unless otherwise noted.)


Characteristics	Figure	Symbol	Min	Typ	Max	Unit
Input Offset Voltage (R <sub>S</sub> = 10 Ω, V <sub>CM</sub> = 0 V, V <sub>O</sub> = 0 V) (V <sub>CC</sub> = +15 V, V <sub>EE</sub> = -15 V) T <sub>A</sub> = +25°C T <sub>A</sub> = -40° to +85°C (V <sub>CC</sub> = 5.0 V, V <sub>EE</sub> = 0) T <sub>A</sub> = +25°C	3	V <sub>IO</sub>	—	0.1 — —	1.0 1.8 2.0	mV
Average Temperature Coefficient of Input Offset Voltage R <sub>S</sub> = 10 Ω, V <sub>CM</sub> = 0 V, V <sub>O</sub> = 0 V, T <sub>A</sub> = -40° to +85°C	3	ΔV <sub>IO</sub> /ΔT	—	2.0	—	μV/°C
Input Bias Current (V <sub>CM</sub> = 0 V, V <sub>O</sub> = 0 V) T <sub>A</sub> = +25°C T <sub>A</sub> = -40° to +85°C	4, 5	I <sub>IB</sub>	— —	300 —	650 800	nA
Input Offset Current (V <sub>CM</sub> = 0 V, V <sub>O</sub> = 0 V) T <sub>A</sub> = +25°C T <sub>A</sub> = -40° to +85°C		I <sub>IO</sub>	— —	3.0 —	65 80	nA
Common Mode Input Voltage Range (ΔV <sub>IO</sub> = 5.0 mV, V <sub>O</sub> = 0 V) T <sub>A</sub> = +25°C	6	V <sub>ICR</sub>	V <sub>EE</sub> to (V <sub>CC</sub> - 1.8)			V
Large Signal Voltage Gain (V <sub>O</sub> = 0 V to 10 V, R <sub>L</sub> = 2.0 kΩ) T <sub>A</sub> = +25°C T <sub>A</sub> = -40° to +85°C	7	A <sub>VOL</sub>	90 86	100 —	—	dB
Output Voltage Swing (V <sub>ID</sub> = ±1.0 V) (V <sub>CC</sub> = +15 V, V <sub>EE</sub> = -15 V) R <sub>L</sub> = 2.0 kΩ R <sub>L</sub> = 2.0 kΩ R <sub>L</sub> = 10 kΩ R <sub>L</sub> = 10 kΩ (V <sub>CC</sub> = 5.0 V, V <sub>EE</sub> = 0 V) R <sub>L</sub> = 2.0 kΩ R <sub>L</sub> = 2.0 kΩ	8, 9, 12 10, 11	V <sub>O+</sub> V <sub>O-</sub> V <sub>O+</sub> V <sub>O-</sub>  V <sub>OL</sub> V <sub>OH</sub>	13.4 — 13.4 —  — 3.7	13.9 -13.9 14 -14.7  — —	— -13.5 — -14.1  0.2 5.0	V
Common Mode Rejection (V <sub>in</sub> = +13.2 V to -15 V)	13	CMR	80	100	—	dB
Power Supply Rejection V <sub>CC</sub> /V <sub>EE</sub> = +15 V/-15 V, +5.0 V/-15 V, +15 V/-5.0 V	14, 15	PSR	80	105	—	dB
Output Short Circuit Current (V <sub>ID</sub> = 1.0 V, Output to Ground) Source Sink	16	I <sub>SC</sub>	+25 -25	+37 -37	—	mA
Power Supply Current Per Amplifier (V <sub>O</sub> = 0 V) (V <sub>CC</sub> = +15 V, V <sub>EE</sub> = -15 V) T <sub>A</sub> = +25°C T <sub>A</sub> = -40° to +85°C (V <sub>CC</sub> = 5.0 V, V <sub>EE</sub> = 0 V) T <sub>A</sub> = +25°C	17	I <sub>CC</sub>	— — —	2.15 — —	2.75 3.0 2.75	mA

# MC33272A MC33274A







**AC ELECTRICAL CHARACTERISTICS** ( $V_{CC} = +15 \text{ V}$ ,  $V_{EE} = -15 \text{ V}$ ,  $T_A = 25^\circ\text{C}$ , unless otherwise noted.)

Characteristics	Figure	Symbol	Min	Typ	Max	Unit
Slew Rate ( $V_{in} = -10 \text{ V}$ to $+10 \text{ V}$ , $R_L = 2.0 \text{ k}\Omega$ , $C_L = 100 \text{ pF}$ , $A_V = +1.0 \text{ V}$ )	18, 33	SR	8.0	10	—	$\text{V}/\mu\text{s}$
Gain Bandwidth Product ( $f = 100 \text{ kHz}$ )	19	GBW	17	24	—	MHz
AC Voltage Gain ( $R_L = 2.0 \text{ k}\Omega$ , $V_O = 0 \text{ V}$ , $f = 20 \text{ kHz}$ )	20, 21, 22	AVO	—	65	—	dB
Unity Gain Frequency (Open Loop)		$f_U$	—	5.5	—	MHz
Gain Margin ( $R_L = 2.0 \text{ k}\Omega$ , $C_L = 0 \text{ pF}$ )	23, 24, 26	$A_m$	—	12	—	dB
Phase Margin ( $R_L = 2.0 \text{ k}\Omega$ , $C_L = 0 \text{ pF}$ )	23, 25, 26	$\phi_m$	—	55	—	Degrees
Channel Separation ( $f = 20 \text{ Hz}$ to $20 \text{ kHz}$ )	27	CS	—	-120	—	dB
Power Bandwidth ( $V_O = 20 \text{ V}_{pp}$ , $R_L = 2.0 \text{ k}\Omega$ , THD $\leq 1.0\%$ )		BWP	—	160	—	kHz
Total Harmonic Distortion ( $R_L = 2.0 \text{ k}\Omega$ , $f = 20 \text{ Hz}$ to $20 \text{ kHz}$ , $V_O = 3.0 \text{ V}_{rms}$ , $A_V = +1.0$ )	28	THD	—	0.003	—	%
Open Loop Output Impedance ( $V_O = 0 \text{ V}$ , $f = 6.0 \text{ MHz}$ )	29	$ Z_{OL} $	—	35	—	$\Omega$
Differential Input Resistance ( $V_{CM} = 0 \text{ V}$ )		$R_{IN}$	—	16	—	$M\Omega$
Differential Input Capacitance ( $V_{CM} = 0 \text{ V}$ )		$C_{IN}$	—	3.0	—	pF
Equivalent Input Noise Voltage ( $R_S = 100 \Omega$ , $f = 1.0 \text{ kHz}$ )	30	$e_n$	—	18	—	$\text{nV}/\sqrt{\text{Hz}}$
Equivalent Input Noise Current ( $f = 1.0 \text{ kHz}$ )	31	$i_n$	—	0.5	—	$\text{pA}/\sqrt{\text{Hz}}$

**Figure 1. Equivalent Circuit Schematic  
(Each Amplifier)**




# MC33272A MC33274A




# MC33272A MC33274A


**Figure 8. Split Supply Output Voltage Swing versus Supply Voltage**




**Figure 9. Split Supply Output Saturation Voltage versus Load Current**




**Figure 10. Single Supply Output Saturation Voltage versus Load Resistance to Ground**




**Figure 11. Single Supply Output Saturation Voltage versus Load Resistance to  $V_{CC}$**



**Figure 12. Output Voltage versus Frequency**




**Figure 13. Common Mode Rejection versus Frequency**




# MC33272A MC33274A


**Figure 14. Positive Power Supply Rejection versus Frequency**




**Figure 15. Negative Power Supply Rejection versus Frequency**




**Figure 16. Output Short Circuit Current versus Temperature**




**Figure 17. Supply Current versus Supply Voltage**



**Figure 18. Normalized Slew Rate versus Temperature**




**Figure 19. Gain Bandwidth Product versus Temperature**




# MC33272A MC33274A


**Figure 20. Voltage Gain and Phase versus Frequency**




**Figure 21. Gain and Phase versus Frequency**




**Figure 22. Open Loop Voltage Gain and Phase versus Frequency**




**Figure 23. Open Loop Gain Margin and Phase Margin versus Output Load Capacitance**



**Figure 24. Open Loop Gain Margin versus Temperature**




**Figure 25. Phase Margin versus Temperature**




# MC33272A MC33274A


**Figure 26. Phase Margin and Gain Margin versus Differential Source Resistance**




**Figure 27. Channel Separation versus Frequency**




**Figure 28. Total Harmonic Distortion versus Frequency**




**Figure 29. Output Impedance versus Frequency**



**Figure 30. Input Referred Noise Voltage versus Frequency**




**Figure 31. Input Referred Noise Current versus Frequency**




## MC33272A MC33274A


**Figure 32. Percent Overshoot versus Load Capacitance**




**Figure 33. Noninverting Amplifier Slew Rate for the MC33274**




**Figure 34. Noninverting Amplifier Overshoot for the MC33274**



**Figure 35. Small Signal Transient Response for MC33274**




**Figure 36. Large Signal Transient Response for MC33274**



# MC33272A MC33274A

## OUTLINE DIMENSIONS

**P SUFFIX**  
PLASTIC PACKAGE  
CASE 626-05  
ISSUE K




NOTES:

1. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL.
2. PACKAGE CONTOUR OPTIONAL (ROUND OR SQUARE CORNERS).
3. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	9.40	10.16	0.370	0.400
B	6.10	6.60	0.240	0.260
C	3.94	4.45	0.155	0.175
D	0.38	0.51	0.015	0.020
F	1.02	1.78	0.040	0.070
G	2.54 BSC		0.100 BSC	
H	0.76	1.27	0.030	0.050
J	0.20	0.30	0.008	0.012
K	2.92	3.43	0.115	0.135
L	7.62 BSC		0.300 BSC	
M	—	10°	—	10°
N	0.76	1.01	0.030	0.040

**D SUFFIX**  
PLASTIC PACKAGE  
CASE 751-05  
(SO-8)  
ISSUE R



NOTES:


1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. DIMENSIONS ARE IN MILLIMETERS.
3. DIMENSION D AND E DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 PER SIDE.
5. DIMENSION B DOES NOT INCLUDE MOLD PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 TOTAL IN EXCESS OF THE B DIMENSION AT MAXIMUM MATERIAL CONDITION.

DIM	MILLIMETERS	
	MIN	MAX
A	1.35	1.75
A1	0.10	0.25
B	0.35	0.49
C	0.18	0.25
D	4.80	5.00
E	3.80	4.00
e	1.27 BSC	
H	5.80	6.20
h	0.25	0.50
L	0.40	1.25
θ	0°	7°

# MC33272A MC33274A

## OUTLINE DIMENSIONS


**P SUFFIX**  
PLASTIC PACKAGE  
CASE 646-06  
ISSUE L



- NOTES:
- LEADS WITHIN 0.13 (0.005) RADIUS OF TRUE POSITION AT SEATING PLANE AT MAXIMUM MATERIAL CONDITION.
  - DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
  - DIMENSION B DOES NOT INCLUDE MOLD FLASH.
  - ROUNDED CORNERS OPTIONAL.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.715	0.770	18.16	19.56
B	0.240	0.260	6.10	6.60
C	0.145	0.185	3.69	4.69
D	0.015	0.021	0.38	0.53
F	0.040	0.070	1.02	1.78
G	0.100 BSC		2.54 BSC	
H	0.052	0.095	1.32	2.41
J	0.008	0.015	0.20	0.38
K	0.115	0.135	2.92	3.43
L	0.300 BSC		7.62 BSC	
M	0°	10°	0°	10°
N	0.015	0.039	0.39	1.01

**D SUFFIX**  
PLASTIC PACKAGE  
CASE 751A-03  
(SO-14)  
ISSUE F



- NOTES:
- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  - CONTROLLING DIMENSION: MILLIMETER.
  - DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
  - MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
  - DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	8.55	8.75	0.337	0.344
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.054	0.068
D	0.35	0.49	0.014	0.019
F	0.40	1.25	0.016	0.049
G	1.27 BSC		0.050 BSC	
J	0.19	0.25	0.008	0.009
K	0.10	0.25	0.004	0.009
M	0°	7°	0°	7°
P	5.80	6.20	0.228	0.244
R	0.25	0.50	0.010	0.019

# MC33272A MC33274A

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and  are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

**How to reach us:**

**USA/EUROPE/Locations Not Listed:** Motorola Literature Distribution;  
P.O. Box 20912; Phoenix, Arizona 85036. 1-800-441-2447 or 602-303-5454

**MFAX:** RMFAX0@email.sps.mot.com – **TOUCHTONE** 602-244-6609  
**INTERNET:** <http://Design-NET.com>

**JAPAN:** Nippon Motorola Ltd.; Tatsumi-SPD-JLDC, 6F Seibu-Butsuryu-Center,  
3-14-2 Tatsumi Koto-Ku, Tokyo 135, Japan. 03-81-3521-8315

**ASIA/PACIFIC:** Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,  
51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852-26629298



MC33272A/D

