



NPN Silicon Low Noise Transistor

The MRF1047T1 is fabricated utilizing Motorola's latest 12 GHz f_t discrete bipolar silicon process. The minimum noise figure is 1.0 dB at $V_{CE} = 3.0$ V and $I_C = 3.0$ mA. The noise performance of the MRF1047T1 at low bias makes this device the ideal choice in high gain, low noise applications. This device is well suited for low-voltage, low-current, front-end applications, for use in pagers, cellular and cordless phones, and other portable wireless systems.

The MRF1047T1 has 16 emitter fingers, with self-aligned and enhanced processing, resulting in a high f_t , low operating current transistor with reduced parasitics. The MRF1047T1 is fully-ion implanted with gold metallization and nitride passivation for maximum device reliability, performance and uniformity.

- Low Noise Figure, $NF_{min} = 1.0$ dB (Typ) @ 1.0 GHz, 3.0 V and 3.0 mA
- High Current Gain-Bandwidth Product, $f_t = 12$ GHz, 3.0 V @ 15 mA
- Maximum Stable Gain, 17 dB @ 1.0 GHz, 3.0 V and 10 mA
- Output Third Order Intercept, $OIP_3 = 26$ dBm @ 1.0 GHz 3.0 V and 15 mA
- Fully Ion-Implanted with Gold Metallization and Nitride Passivation

MAXIMUM RATINGS

| Rating | Symbol | Value | Unit |
|---|--------------|--------------|------------|
| Collector-Emitter Voltage | V_{CEO} | 5.0 | Vdc |
| Collector-Base Voltage | V_{CBO} | 12 | Vdc |
| Emitter-Base Voltage | V_{EBO} | 2.5 | Vdc |
| Collector Current – Continuous [Note 3] | I_C | 45 | mA |
| Power Dissipation @ $T_C = 75^\circ\text{C}$ Derate Linearly above $T_C = 75^\circ\text{C}$ at | $P_{D(max)}$ | 0.172 2.3 | W mW/°C |
| Storage Temperature Range | T_{stg} | -55 to 150 | °C |
| Maximum Junction Temperature | $T_{J(max)}$ | 150 | °C |

NOTES: 1. Meets Human Body Model (HBM) ≤ 300 V and Machine Model (MM) ≤ 75 V.
2. ESD data available upon request.
3. For MTBF >10 years.

THERMAL CHARACTERISTIC

| Characteristics | Symbol | Max | Unit |
|--------------------------------------|-----------------|-----|------|
| Thermal Resistance, Junction-to-Case | $R_{\theta JC}$ | 435 | °C/W |

NOTE: To calculate the junction temperature use $T_J = (P_D \times R_{\theta JC}) + T_C$. The case temperature measured on collector lead adjacent to the package body.

Order this document by MRF1047T1/D


MRF1047T1

RF NPN SILICON TRANSISTOR

$f_t = 12$ GHz
 $NF_{min} = 1.0$ dB
 $I_{CMAX} = 45$ mA
 $V_{CEO} = 5.0$ V

SEMICONDUCTOR TECHNICAL DATA

Pin 1. Base
2. Emitter
3. Collector



PLASTIC PACKAGE
CASE 419
(SC-70, Tape & Reel Only)

ORDERING INFORMATION

| Device | Marking | Package |
|-----------|---------|-----------------------|
| MRF1047T1 | WB | SC-70 Tape & Reel* |

*3,000 Units per 8 mm, 7 inch reel.

LIFETIME BUY

LAST SHIP: 26MAR02
LAST ORDER: 03AUG01

MRF1047T1

ELECTRICAL CHARACTERISTICS (T_C = 25°C, unless otherwise noted)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|--|--------------------------------|--------|------------|--------|------|
| OFF CHARACTERISTICS [Note 1] | | | | | |
| Collector–Emitter Breakdown Voltage (I _C = 0.1 mA, I _B = 0) | V _{(BR)CEO} | 5.0 | – | – | Vdc |
| Collector–Base Breakdown Voltage (I _C = 0.1 mA, I _E = 0) | V _{(BR)CBO} | 12 | – | – | Vdc |
| Emitter–Base Breakdown Voltage (I _E = 0.1 mA, I _C = 0) | V _{(BR)CBO} | 2.5 | – | – | Vdc |
| Collector Cutoff Current (V _{CB} = 1.0 V, I _E = 0) | I _{CBO} | – | – | 0.2 | μA |
| Emitter Cutoff Current (V _{EB} = 1.0 V, I _C = 0) | I _{EBO} | – | – | 0.1 | μA |
| ON CHARACTERISTICS [Note 1] | | | | | |
| DC Current Gain (V _{CE} = 3.0 V, I _C = 3.0 mA) | h _{FE} | 100 | – | 300 | – |
| DYNAMIC CHARACTERISTICS | | | | | |
| Collector–Base Capacitance (V _{CB} = 1.0 Vdc, I _E = 0, f = 1.0 MHz) | C _{cb} | – | 0.4 | – | pF |
| Current–Gain Bandwidth Product (V _{CE} = 3.0 Vdc, I _C = 15 mA, f = 1.0 GHz) | f _t | – | 12 | – | GHz |
| PERFORMANCE CHARACTERISTICS | | | | | |
| Insertion Gain V _{CE} = 1.0 V, I _C = 1.0 mA, f = 1.0 GHz V _{CE} = 3.0 V, I _C = 3.0 mA, f = 1.0 GHz | S ₂₁ ² | – – | 8.0 13 | – – | dB |
| Maximum Stable Gain and/or Maximum Available Gain [Note 2] V _{CE} = 1.0 V, I _C = 1.0 mA, f = 1.0 GHz V _{CE} = 3.0 V, I _C = 3.0 mA, f = 1.0 GHz | MSG, MAG | – – | 11 16 | – – | dB |
| Minimum Noise Figure V _{CE} = 1.0 V, I _C = 1.0 mA, f = 1.0 GHz V _{CE} = 3.0 V, I _C = 3.0 mA, f = 1.0 GHz | NF _{min} | – – | 1.2 1.0 | – – | dB |
| Associated Gain at Minimum NF V _{CE} = 1.0 V, I _C = 1.0 mA, f = 1.0 GHz V _{CE} = 3.0 V, I _C = 3.0 mA, f = 1.0 GHz | G _{NF} | – – | 10 13 | – – | dB |
| Output Power at 1.0 dB Gain Compression [Note 3] (V _{CE} = 3.0 V, I _C = 3.0 mA, f = 1.0 GHz) | P _{1dB} | – | 0.5 | – | dBm |
| Output Third Order Intercept [Note 3] (V _{CE} = 3.0 V, I _C = 3.0 mA, f = 1.0 GHz) | OIP ₃ | – | 22 | – | dBm |

NOTES: 1. Pulse width ≤300 μs, duty cycle ≤2% pulsed.

2. Maximum Available Gain and Maximum Stable Gain are defined by the K factor as follows:

$$\text{MAG} = \left| \frac{S_{21}}{S_{12}} \left(K \pm \sqrt{K^2 - 1} \right) \right|, \text{ if } K > 1, \text{ MSG} = \left| \frac{S_{21}}{S_{12}} \right|, \text{ if } K < 1$$

3. Z_{in} = 50 Ω and Z_{out} matched for optimum IP3.

LIFETIME BUY

LAST SHIP: 26MAR02
LAST ORDER: 03AUG01

MRF1047T1

Figure 1. Capacitance versus Voltage




Figure 2. Input Capacitance versus Voltage




Figure 3. DC Current Gain versus Collector Current




Figure 4. Gain-Bandwidth Product versus Collector Current











Figure 5. Functional Circuit Schematic



LIFETIME BUY

LAST SHIP: 26MAR02
LAST ORDER: 03AUG01



LIFETIME BUY

LAST SHIP: 26MAR02
LAST ORDER: 03AUG01

MRF1047T1

Figure 12. Minimum Noise Figure and Associated Gain versus Collector Current




Figure 13. Minimum Noise Figure and Associated Gain versus Collector Current





Figure 14. Output Third Order Intercept and Output Power at 1.0 dB Gain Compression versus Collector Current



LIFETIME BUY

LAST SHIP: 26MAR02
LAST ORDER: 03AUG01

MRF1047T1

Table 1. Common Emitter S-Parameters

| V _{CE} (Vdc) | I _c (mA) | f (GHz) | S ₁₁ | | S ₂₁ | | S ₁₂ | | S ₂₂ | | K | |
|--------------------------|------------------------|------------|-----------------|-------|-----------------|-------|-----------------|-------|-----------------|-------|------|------|
| | | | S ₁₁ | ∠ φ | S ₂₁ | ∠ φ | S ₁₂ | ∠ φ | S ₂₂ | ∠ φ | | |
| 1.0 | 1.0 | 0.1 | 0.973 | -10 | 3.49 | 171 | 0.029 | 84 | 0.987 | -6 | 0.04 | |
| | | 0.3 | 0.938 | -30 | 3.35 | 154 | 0.082 | 72 | 0.952 | -17 | 0.12 | |
| | | 0.5 | 0.875 | -48 | 3.03 | 137 | 0.124 | 60 | 0.877 | -25 | 0.27 | |
| | | 0.7 | 0.770 | -64 | 2.75 | 124 | 0.153 | 51 | 0.812 | -33 | 0.36 | |
| | | 0.9 | 0.685 | -79 | 2.51 | 112 | 0.174 | 45 | 0.745 | -39 | 0.45 | |
| | | 1.0 | 0.649 | -85 | 2.40 | 107 | 0.181 | 42 | 0.717 | -42 | 0.49 | |
| | | 1.3 | 0.555 | -105 | 2.09 | 92 | 0.195 | 36 | 0.639 | -48 | 0.64 | |
| | | 1.5 | 0.509 | -117 | 1.92 | 84 | 0.202 | 33 | 0.601 | -53 | 0.72 | |
| | | 1.8 | 0.454 | -136 | 1.72 | 72 | 0.204 | 30 | 0.553 | -58 | 0.85 | |
| | | 2.0 | 0.434 | -148 | 1.59 | 66 | 0.205 | 30 | 0.531 | -62 | 0.92 | |
| | | 2.5 | 0.417 | -175 | 1.38 | 50 | 0.208 | 32 | 0.477 | -73 | 1.09 | |
| | | 3.0 | 0.403 | 164 | 1.23 | 39 | 0.227 | 37 | 0.457 | -83 | 1.14 | |
| | | 3.5 | 0.416 | 142 | 1.10 | 28 | 0.259 | 41 | 0.454 | -93 | 1.12 | |
| | | 4.0 | 0.442 | 125 | 1.00 | 20 | 0.310 | 43 | 0.448 | -105 | 1.05 | |
| | | 4.5 | 0.454 | 109 | 0.95 | 12 | 0.378 | 41 | 0.433 | -118 | 0.99 | |
| | 5.0 | 0.478 | 96 | 0.89 | 6 | 0.445 | 37 | 0.437 | -133 | 0.95 | | |
| | 3.0 | 3.0 | 0.1 | 0.917 | -17 | 9.30 | 165 | 0.028 | 80 | 0.955 | -11 | 0.10 |
| | | | 0.3 | 0.792 | -48 | 7.94 | 140 | 0.072 | 65 | 0.831 | -29 | 0.26 |
| | | | 0.5 | 0.630 | -69 | 6.31 | 121 | 0.098 | 56 | 0.674 | -39 | 0.47 |
| | | | 0.7 | 0.505 | -87 | 5.11 | 107 | 0.116 | 51 | 0.571 | -45 | 0.62 |
| | | | 0.9 | 0.418 | -103 | 4.26 | 97 | 0.131 | 50 | 0.498 | -49 | 0.74 |
| | | | 1.0 | 0.388 | -110 | 3.93 | 93 | 0.138 | 49 | 0.471 | -50 | 0.78 |
| | | | 1.3 | 0.317 | -129 | 3.20 | 82 | 0.158 | 49 | 0.406 | -54 | 0.91 |
| | | | 1.5 | 0.289 | -142 | 2.84 | 76 | 0.172 | 48 | 0.380 | -58 | 0.96 |
| | | | 1.8 | 0.265 | -161 | 2.45 | 67 | 0.192 | 48 | 0.346 | -62 | 1.02 |
| | | | 2.0 | 0.260 | -173 | 2.24 | 61 | 0.206 | 48 | 0.329 | -65 | 1.05 |
| | | | 2.5 | 0.282 | 164 | 1.88 | 49 | 0.244 | 47 | 0.284 | -76 | 1.07 |
| | | | 3.0 | 0.283 | 147 | 1.65 | 39 | 0.287 | 45 | 0.271 | -85 | 1.07 |
| | | | 3.5 | 0.306 | 128 | 1.47 | 30 | 0.330 | 42 | 0.269 | -95 | 1.04 |
| | | | 4.0 | 0.334 | 115 | 1.34 | 21 | 0.374 | 38 | 0.262 | -107 | 1.02 |
| 4.5 | | | 0.354 | 103 | 1.25 | 13 | 0.423 | 34 | 0.256 | -119 | 0.99 | |
| 5.0 | 0.382 | 93 | 1.176 | 6 | 0.470 | 29 | 0.260 | -133 | 0.97 | | | |
| 5.0 | 5.0 | 0.1 | 0.861 | -23 | 13.74 | 160 | 0.027 | 78 | 0.923 | -15 | 0.15 | |
| | | 0.3 | 0.671 | -59 | 10.50 | 130 | 0.064 | 63 | 0.727 | -36 | 0.38 | |
| | | 0.5 | 0.489 | -81 | 7.68 | 112 | 0.085 | 57 | 0.552 | -44 | 0.62 | |
| | | 0.7 | 0.379 | -100 | 5.95 | 100 | 0.103 | 56 | 0.455 | -48 | 0.77 | |
| | | 0.9 | 0.311 | -115 | 4.82 | 92 | 0.119 | 55 | 0.393 | -50 | 0.87 | |
| | | 1.0 | 0.289 | -122 | 4.41 | 88 | 0.128 | 55 | 0.372 | -51 | 0.90 | |
| | | 1.3 | 0.241 | -143 | 3.53 | 78 | 0.153 | 55 | 0.323 | -54 | 0.98 | |
| | | 1.5 | 0.223 | -155 | 3.11 | 72 | 0.171 | 55 | 0.303 | -57 | 1.01 | |
| | | 1.8 | 0.214 | -175 | 2.66 | 65 | 0.197 | 54 | 0.277 | -62 | 1.04 | |
| | | 2.0 | 0.217 | 174 | 2.43 | 60 | 0.215 | 53 | 0.263 | -65 | 1.05 | |
| | | 2.5 | 0.251 | 154 | 2.03 | 49 | 0.260 | 50 | 0.222 | -77 | 1.06 | |
| | | 3.0 | 0.256 | 138 | 1.77 | 39 | 0.306 | 46 | 0.213 | -86 | 1.05 | |
| | | 3.5 | 0.282 | 122 | 1.58 | 30 | 0.351 | 42 | 0.212 | -97 | 1.03 | |
| | | 4.0 | 0.310 | 110 | 1.44 | 22 | 0.395 | 37 | 0.205 | -111 | 1.01 | |
| | | 4.5 | 0.330 | 100 | 1.34 | 14 | 0.440 | 32 | 0.202 | -123 | 1.00 | |
| 5.0 | 0.360 | 91 | 1.26 | 7 | 0.483 | 27 | 0.206 | -138 | 0.98 | | | |
| 3.0 | 3.0 | 0.1 | 0.926 | -13 | 9.03 | 167 | 0.021 | 82 | 0.967 | -8 | 0.10 | |
| | | 0.3 | 0.820 | -37 | 7.99 | 145 | 0.056 | 70 | 0.877 | -22 | 0.26 | |
| | | 0.5 | 0.673 | -55 | 6.60 | 126 | 0.079 | 61 | 0.750 | -30 | 0.48 | |
| | | 0.7 | 0.541 | -69 | 5.47 | 113 | 0.096 | 57 | 0.663 | -34 | 0.62 | |
| | | 0.9 | 0.441 | -80 | 4.63 | 103 | 0.110 | 56 | 0.595 | -38 | 0.73 | |
| | | 1.0 | 0.402 | -85 | 4.30 | 99 | 0.117 | 55 | 0.571 | -39 | 0.78 | |
| | | 1.3 | 0.308 | -100 | 3.53 | 87 | 0.136 | 55 | 0.512 | -42 | 0.90 | |
| | | 1.5 | 0.262 | -109 | 3.16 | 81 | 0.149 | 54 | 0.485 | -45 | 0.95 | |
| | | 1.8 | 0.208 | -126 | 2.73 | 72 | 0.169 | 54 | 0.453 | -48 | 1.01 | |
| | | 2.0 | 0.185 | -139 | 2.50 | 67 | 0.183 | 54 | 0.436 | -51 | 1.03 | |
| | | 2.5 | 0.176 | -172 | 2.11 | 55 | 0.219 | 52 | 0.389 | -59 | 1.06 | |
| | | 3.0 | 0.160 | 165 | 1.85 | 45 | 0.259 | 51 | 0.379 | -66 | 1.05 | |

LIFETIME BUY

LAST ORDER: 03AUG01 LAST SHIP: 26MAR02

MRF1047T1

Table 1. Common Emitter S-Parameters (continued)

| V _{CE} (Vdc) | I _C (mA) | f (GHz) | S ₁₁ | | S ₂₁ | | S ₁₂ | | S ₂₂ | | K |
|--------------------------|------------------------|------------|-----------------|------|-----------------|-----|-----------------|-----|-----------------|------|------|
| | | | S ₁₁ | ∠ φ | S ₂₁ | ∠ φ | S ₁₂ | ∠ φ | S ₂₂ | ∠ φ | |
| | | 3.5 | 0.177 | 137 | 1.65 | 35 | 0.301 | 48 | 0.374 | -74 | 1.03 |
| | | 4.0 | 0.208 | 120 | 1.50 | 27 | 0.346 | 45 | 0.363 | -84 | 1.00 |
| | | 4.5 | 0.228 | 106 | 1.40 | 19 | 0.395 | 41 | 0.354 | -93 | 0.97 |
| | | 5.0 | 0.261 | 96 | 1.32 | 11 | 0.444 | 37 | 0.353 | -105 | 0.94 |
| | 5.0 | 0.1 | 0.884 | -19 | 13.66 | 162 | 0.020 | 80 | 0.941 | -12 | 0.14 |
| | | 0.3 | 0.713 | -49 | 10.92 | 135 | 0.052 | 67 | 0.786 | -28 | 0.37 |
| | | 0.5 | 0.529 | -68 | 8.25 | 116 | 0.071 | 61 | 0.632 | -34 | 0.61 |
| | | 0.7 | 0.406 | -83 | 6.48 | 104 | 0.086 | 59 | 0.546 | -37 | 0.75 |
| | | 0.9 | 0.324 | -95 | 5.31 | 95 | 0.101 | 59 | 0.489 | -38 | 0.85 |
| | | 1.0 | 0.293 | -101 | 4.87 | 92 | 0.108 | 59 | 0.470 | -39 | 0.89 |
| | | 1.3 | 0.223 | -118 | 3.90 | 82 | 0.131 | 59 | 0.426 | -41 | 0.97 |
| | | 1.5 | 0.192 | -129 | 3.45 | 76 | 0.146 | 59 | 0.406 | -44 | 1.00 |
| | | 1.8 | 0.163 | -149 | 2.96 | 68 | 0.169 | 58 | 0.383 | -47 | 1.03 |
| | | 2.0 | 0.155 | -163 | 2.70 | 64 | 0.185 | 57 | 0.369 | -49 | 1.04 |
| | | 2.5 | 0.176 | 168 | 2.25 | 53 | 0.226 | 55 | 0.327 | -58 | 1.05 |
| | | 3.0 | 0.174 | 149 | 1.96 | 43 | 0.269 | 52 | 0.321 | -65 | 1.03 |
| | | 3.5 | 0.198 | 128 | 1.74 | 34 | 0.311 | 48 | 0.317 | -74 | 1.01 |
| | | 4.0 | 0.229 | 115 | 1.59 | 26 | 0.355 | 44 | 0.306 | -84 | 0.99 |
| | | 4.5 | 0.249 | 104 | 1.47 | 18 | 0.400 | 40 | 0.299 | -93 | 0.97 |
| | | 5.0 | 0.279 | 95 | 1.38 | 11 | 0.446 | 35 | 0.297 | -105 | 0.94 |
| | 10.0 | 0.1 | 0.781 | -27 | 21.48 | 155 | 0.019 | 77 | 0.886 | -17 | 0.25 |
| | | 0.3 | 0.530 | -62 | 14.32 | 123 | 0.045 | 66 | 0.648 | -33 | 0.56 |
| | | 0.5 | 0.350 | -79 | 9.81 | 106 | 0.062 | 65 | 0.504 | -35 | 0.80 |
| | | 0.7 | 0.257 | -92 | 7.38 | 96 | 0.078 | 66 | 0.439 | -35 | 0.91 |
| | | 0.9 | 0.198 | -105 | 5.90 | 89 | 0.096 | 66 | 0.401 | -35 | 0.96 |
| | | 1.0 | 0.179 | -110 | 5.37 | 86 | 0.105 | 66 | 0.389 | -36 | 0.98 |
| | | 1.3 | 0.133 | -128 | 4.24 | 78 | 0.131 | 65 | 0.362 | -37 | 1.02 |
| | | 1.5 | 0.114 | -142 | 3.73 | 73 | 0.149 | 64 | 0.348 | -40 | 1.03 |
| | | 1.8 | 0.104 | -166 | 3.18 | 66 | 0.176 | 62 | 0.331 | -43 | 1.03 |
| | | 2.0 | 0.106 | 178 | 2.90 | 62 | 0.194 | 61 | 0.320 | -46 | 1.04 |
| | | 2.5 | 0.144 | 154 | 2.41 | 52 | 0.239 | 57 | 0.280 | -55 | 1.03 |
| | | 3.0 | 0.149 | 137 | 2.09 | 43 | 0.284 | 53 | 0.276 | -62 | 1.02 |
| | | 3.5 | 0.176 | 118 | 1.85 | 35 | 0.327 | 48 | 0.273 | -72 | 1.00 |
| | | 4.0 | 0.208 | 108 | 1.69 | 27 | 0.370 | 43 | 0.260 | -82 | 0.99 |
| | | 4.5 | 0.228 | 99 | 1.56 | 19 | 0.414 | 39 | 0.253 | -92 | 0.97 |
| | | 5.0 | 0.257 | 91 | 1.47 | 12 | 0.457 | 34 | 0.250 | -104 | 0.95 |

LIFETIME BUY

LAST ORDER: 03AUG01 LAST SHIP: 26MAR02

MRF1047T1

Table 2. Common-Emitter Noise Parameters

| V _{CE} (Vdc) | I _c (mA) | f (GHz) | NF _{min} (dB) | Γ _O | | R _N Ω | r _n | G _{NF} (dB) | K | |
|--------------------------|------------------------|------------|---------------------------|----------------|-------|---------------------|----------------|-------------------------|------|------|
| | | | | Magnitude | Angle | | | | | |
| 1.0 | 1.0 | 0.3 | 1.00 | 0.67 | 15 | 28 | 0.55 | 18.6 | 0.12 | |
| | | 0.5 | 1.04 | 0.64 | 25 | 26 | 0.52 | 15.8 | 0.27 | |
| | | 0.7 | 1.08 | 0.61 | 35 | 25 | 0.49 | 13.3 | 0.36 | |
| | | 0.9 | 1.13 | 0.59 | 46 | 23 | 0.46 | 11.2 | 0.45 | |
| | | 1.0 | 1.16 | 0.57 | 51 | 22 | 0.44 | 10.2 | 0.49 | |
| | | 1.5 | 1.28 | 0.52 | 81 | 16 | 0.33 | 6.8 | 0.72 | |
| | | 2.0 | 1.41 | 0.48 | 116 | 10 | 0.20 | 5.5 | 0.92 | |
| | | 2.4 | 1.52 | 0.47 | 146 | 6.0 | 0.12 | 6.0 | 1.07 | |
| | 3.0 | 0.3 | 0.83 | 0.56 | 14 | 17 | 0.34 | 20.9 | 0.26 | |
| | | 0.5 | 0.88 | 0.52 | 23 | 16 | 0.32 | 18.0 | 0.47 | |
| | | 0.7 | 0.94 | 0.48 | 32 | 15 | 0.30 | 15.5 | 0.62 | |
| | | 0.9 | 0.99 | 0.45 | 42 | 14 | 0.29 | 13.3 | 0.74 | |
| | | 1.0 | 1.02 | 0.43 | 47 | 14 | 0.28 | 12.4 | 0.78 | |
| | | 1.5 | 1.16 | 0.38 | 79 | 11 | 0.22 | 8.7 | 0.96 | |
| | | 2.0 | 1.31 | 0.35 | 117 | 8.0 | 0.15 | 7.1 | 1.05 | |
| | | 2.4 | 1.44 | 0.35 | 152 | 5.0 | 0.10 | 7.3 | 1.07 | |
| | 5.0 | 0.3 | 0.90 | 0.48 | 13 | 15 | 0.29 | 21.6 | 0.38 | |
| | | 0.5 | 0.94 | 0.44 | 21 | 14 | 0.28 | 18.8 | 0.62 | |
| | | 0.7 | 0.98 | 0.40 | 31 | 13 | 0.26 | 16.3 | 0.77 | |
| | | 0.9 | 1.03 | 0.36 | 42 | 12 | 0.25 | 14.1 | 0.87 | |
| | | 1.0 | 1.06 | 0.35 | 48 | 12 | 0.24 | 13.1 | 0.90 | |
| | | 1.5 | 1.20 | 0.30 | 82 | 10 | 0.19 | 9.4 | 1.01 | |
| | | 2.0 | 1.37 | 0.28 | 123 | 7.0 | 0.14 | 7.7 | 1.05 | |
| | | 2.4 | 1.53 | 0.30 | 161 | 5.0 | 0.11 | 7.7 | 1.06 | |
| | 3.0 | 1.0 | 0.3 | 1.11 | 0.67 | 14 | 31 | 0.62 | 19.7 | 0.11 |
| | | | 0.5 | 1.12 | 0.65 | 22 | 30 | 0.59 | 16.8 | 0.26 |
| | | | 0.7 | 1.13 | 0.64 | 31 | 28 | 0.56 | 14.3 | 0.35 |
| | | | 0.9 | 1.16 | 0.62 | 41 | 26 | 0.52 | 12.2 | 0.44 |
| 1.0 | | | 1.17 | 0.60 | 46 | 25 | 0.50 | 11.2 | 0.48 | |
| 1.5 | | | 1.26 | 0.56 | 74 | 19 | 0.38 | 7.7 | 0.70 | |
| 2.0 | | | 1.39 | 0.51 | 106 | 12 | 0.24 | 6.5 | 0.91 | |
| 2.4 | | | 1.51 | 0.47 | 135 | 7.0 | 0.15 | 7.0 | 1.05 | |
| 3.0 | | 0.3 | 0.94 | 0.60 | 13 | 21 | 0.41 | 22.3 | 0.26 | |
| | | 0.5 | 0.96 | 0.57 | 19 | 20 | 0.40 | 19.3 | 0.48 | |
| | | 0.7 | 0.98 | 0.54 | 25 | 19 | 0.39 | 16.7 | 0.62 | |
| | | 0.9 | 1.01 | 0.51 | 33 | 18 | 0.36 | 14.5 | 0.73 | |
| | | 1.0 | 1.03 | 0.50 | 37 | 18 | 0.35 | 13.5 | 0.78 | |
| | | 1.5 | 1.13 | 0.44 | 61 | 15 | 0.29 | 9.7 | 0.95 | |
| | | 2.0 | 1.26 | 0.37 | 92 | 11 | 0.21 | 8.1 | 1.03 | |
| | | 2.4 | 1.39 | 0.32 | 121 | 8.0 | 0.15 | 8.3 | 1.06 | |
| 5.0 | | 0.3 | 0.92 | 0.53 | 13 | 17 | 0.34 | 22.8 | 0.37 | |
| | | 0.5 | 0.95 | 0.49 | 20 | 16 | 0.32 | 19.9 | 0.61 | |
| | | 0.7 | 0.99 | 0.46 | 28 | 16 | 0.31 | 17.4 | 0.75 | |
| | | 0.9 | 1.03 | 0.43 | 37 | 15 | 0.29 | 15.2 | 0.85 | |
| | | 1.0 | 1.06 | 0.42 | 42 | 14 | 0.28 | 14.2 | 0.89 | |
| | | 1.5 | 1.20 | 0.36 | 72 | 12 | 0.23 | 10.4 | 1.00 | |
| | | 2.0 | 1.36 | 0.32 | 109 | 8.0 | 0.17 | 8.7 | 1.04 | |
| | | 2.4 | 1.53 | 0.30 | 144 | 6.0 | 0.12 | 8.8 | 1.05 | |
| 10.0 | | 0.3 | 1.17 | 0.39 | 13 | 15 | 0.29 | 23.8 | 0.56 | |
| | | 0.5 | 1.18 | 0.35 | 21 | 14 | 0.28 | 20.9 | 0.80 | |
| | | 0.7 | 1.21 | 0.32 | 31 | 13 | 0.26 | 18.3 | 0.91 | |
| | | 0.9 | 1.24 | 0.29 | 42 | 13 | 0.25 | 16.1 | 0.96 | |
| | | 1.0 | 1.26 | 0.28 | 48 | 12 | 0.25 | 15.1 | 0.98 | |
| | | 1.5 | 1.40 | 0.24 | 83 | 10 | 0.21 | 11.2 | 1.03 | |
| | | 2.0 | 1.59 | 0.23 | 128 | 8.0 | 0.16 | 9.3 | 1.04 | |
| | | 2.4 | 1.79 | 0.24 | 170 | 7.0 | 0.13 | 9.3 | 1.03 | |

LIFETIME BUY


LAST SHIP: 26MAR02
LAST ORDER: 03AUG01

MRF1047T1

Table 3. Spice Parameters (MRF1047 Die Gummel-Poon Parameters)

| Name | Value | Name | Value | Name | Value |
|------|-----------|------|----------|------|----------|
| IS | 5.8 E-16 | IRB | 7.50E-03 | TF | 1.50E-11 |
| BF | 180 | RBM | 4.0 | XTF | 8.0 |
| NF | 0.99 | RE | 1.0 | VTF | 4.2355 |
| VAF | 40 | RC | 7.0 | ITF | 0.2 |
| IKF | 0.18 | XTB | 0 | PTF | 60 |
| ISE | 3.140E-14 | EG | 1.11 | TR | 1.00E-09 |
| NE | 1.78 | XTI | 3.0 | FC | 0.95 |
| BR | 26.8 | CJE | 5.70E-13 | | |
| NR | 0.9974 | VJE | 0.98 | | |
| VAR | 2.0 | MJE | 0.5 | | |
| IKR | 7.50E-03 | CJC | 4.00E-13 | | |
| ISC | 2.200E-14 | VJC | 0.59 | | |
| NC | 1.48 | MJC | 0.314 | | |
| RB | 6.924 | XCJC | 0.6 | | |


Figure 15. MRF1047 SC-70 Package Equivalent Circuit



LIFETIME BUY

LAST SHIP: 26MAR02
LAST ORDER: 03AUG01


Figure 16. Constant Gain and Noise Figure Contours
(f = 1.0 GHz)



$V_{CE} = 1.0\text{ V}$
 $I_C = 1.0\text{ mA}$
 □ — Potentially Unstable

| f (GHz) | NF Opt (dB) | Γ_o | Rn | K |
|---------|-------------|--------------------------|------|------|
| 1.0 | 1.16 | $0.57 \angle 51.3^\circ$ | 21.8 | 0.49 |

Figure 17. Constant Gain and Noise Figure Contours
(f = 2.0 GHz)



$V_{CE} = 1.0\text{ V}$
 $I_C = 1.0\text{ mA}$
 □ — Potentially Unstable


| f (GHz) | NF Opt (dB) | Γ_o | Rn | K |
|---------|-------------|---------------------------|-----|------|
| 2.0 | 1.41 | $0.48 \angle 115.6^\circ$ | 9.8 | 0.92 |

LIFETIME BUY

LAST SHIP: 26MAR02
 LAST ORDER: 03AUG01

MRF1047T1


**Figure 18. Constant Gain and Noise Figure Contours
(f = 1.0 GHz)**



$V_{CE} = 3.0\text{ V}$
 $I_C = 3.0\text{ mA}$
 □ — Potentially Unstable

| f (GHz) | NF Opt (dB) | Γ_o | Rn | K |
|---------|-------------|--------------------------|------|------|
| 1.0 | 1.03 | $0.50 \angle 37.1^\circ$ | 17.6 | 0.78 |

**Figure 19. Constant Gain and Noise Figure Contours
(f = 2.0 GHz)**



$V_{CE} = 3.0\text{ V}$
 $I_C = 3.0\text{ mA}$
 □ — Potentially Unstable

| f (GHz) | NF Opt (dB) | Γ_o | Rn | K |
|---------|-------------|--------------------------|------|------|
| 2.0 | 1.26 | $0.37 \angle 91.7^\circ$ | 10.7 | 1.03 |


LIFETIME BUY

LAST SHIP: 26MAR02
LAST ORDER: 03AUG01

MRF1047T1

OUTLINE DIMENSIONS

PLASTIC PACKAGE
CASE 419-02
(SC-70)
ISSUE J




- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

| DIM | INCHES | | MILLIMETERS | |
|-----|-----------|-------|-------------|------|
| | MIN | MAX | MIN | MAX |
| A | 0.071 | 0.087 | 1.80 | 2.20 |
| B | 0.045 | 0.053 | 1.15 | 1.35 |
| C | 0.035 | 0.049 | 0.90 | 1.25 |
| D | 0.012 | 0.016 | 0.30 | 0.40 |
| G | 0.047 | 0.055 | 1.20 | 1.40 |
| H | 0.000 | 0.004 | 0.00 | 0.10 |
| J | 0.004 | 0.010 | 0.10 | 0.25 |
| K | 0.017 REF | | 0.425 REF | |
| L | 0.026 BSC | | 0.650 BSC | |
| N | 0.028 REF | | 0.700 REF | |
| R | 0.031 | 0.039 | 0.80 | 1.00 |
| S | 0.079 | 0.087 | 2.00 | 2.20 |
| V | 0.012 | 0.016 | 0.30 | 0.40 |

LIFETIME BUY

LAST SHIP: 26MAR02

LAST ORDER: 03AUG01

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and  are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

How to reach us:

USA/EUROPE/Locations Not Listed: Motorola Literature Distribution;
P.O. Box 5405, Denver, Colorado 80217. 1-303-675-2140 or 1-800-441-2447

JAPAN: Motorola Japan Ltd.; SPS, Technical Information Center, 3-20-1,
Minami-Azabu, Minato-ku, Tokyo 106-8573 Japan. 81-3-3440-3569

Technical Information Center: 1-800-521-6274

ASIA/PACIFIC: Motorola Semiconductors H.K. Ltd.; Silicon Harbour Centre,
2, Dai King Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong.
852-26668334

HOME PAGE: <http://www.motorola.com/semiconductors/>



MRF1047T1/D