



Micro Commercial Components

Micro Commercial Components
 20736 Marilla Street Chatsworth
 CA 91311
 Phone: (818) 701-4933
 Fax: (818) 701-4939

SMD22PL THRU SMD26PL

Schottky Barrier Diodes 20 to 60 Volts

Features

- High Surge Capability
- Low Forward Voltage
- Low Profile Package

Mechanical Data

- Packaging: Powerlite-123
- Marking Code : SMD22PL---M2
 SMD24PL---M4
 SMD26PL---M6

Maximum Ratings

Symbol	Rating	Rating	Unit
V _R	Maximum RMS Voltage	SMD22PL	14
		SMD24PL	28
		SMD26PL	42
V _{RRM}	Repetitive Peak Reverse Voltage	SMD22PL	20
		SMD24PL	40
		SMD26PL	60
I _{F(AV)}	Rectified Current (Average) Half Wave Rectification with Resist. Load at T _L =90°C	2.0	A
I _{FSM}	Surge Forward Current, halfsine wave 8.3ms	50	A
R _{thJL}	Typical Thermal Resistance ⁽¹⁾	80	°C / W
T _J	Junction Temperature	-65 to +125	°C
T _{STG}	Storage Temperature	-65 to +125	°C

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Typ	Max	Units
V _F	Forward Voltage (@2A dc)	SMD22PL	---	0.50	V
		SMD24PL	---	0.50	
		SMD26PL	---	0.70	
I _R	Maximum DC Reverse Current	---	---	0.5	mA
C _J	Typical Junction Capacitance @f=1.0MHz, V _r =4V	---	210	---	pF

Tnote: Thermal Resistance: PC Board Mounted on 0.2*0.2"(5*5mm) copper pad area.

Powerlite-123

DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.140	.152	3.55	3.85	
B	.100	.112	2.55	2.85	
C	.055	.071	1.40	1.80	
D	.037	.053	0.95	1.35	
E	.020	.039	0.50	1.00	
G	.010	-----	0.25	-----	
H	-----	.008	----	.20	

SUGGESTED SOLDER PAD LAYOUT