

ST - 1KA · ST - 1KB

The ST - 1KA and 1KB are high - sensitivity NPN silicon phototransistors mounted in durable, hermetically sealed TO - 18 metal cans, which provide years of reliable performance, even under demanding conditions such as use out - doors.

FEATURES


- Wide angular response
- Durable
- High reliability in demanding environments
- Two leads (Collector, Emitter) ST - 1KA
- Three leads (Collector Emitter, Base) ST - 1KB

APPLICATIONS

- Optical counters
- Optical detectors
- Infrared sensors
- Fiber optic communications

DIMENSIONS

(Unit : mm)



MAXIMUM RATINGS

(Ta=25 °C)

| Item | Symbol | Rating | Unit |
|-----------------------------|-------------------|-------------|------|
| C - E voltage | V _{CEO} | 40 | V |
| E - C voltage | V _{ECO} | 4 | V |
| Collector current | I _c | 50 | mA |
| Collector power dissipation | P _c | 150 | mW |
| Operating temp. | T _{opr.} | - 30 ~ +100 | |
| Storage Temp. | T _{stg.} | - 50 ~ +150 | |
| Soldering temp. *1 | T _{sol.} | 260 | |

*1. For MAX. 5 seconds at the position of 2 mm from the package

ELECTRO-OPTICAL CHARACTERISTICS

(Ta=25 °C)


| Item | Symbol | Conditions | Min. | Typ. | Max. | Unit. |
|--------------------------|----------------------|---|------|-------------|------|-------|
| Collector dark current | I _{CEO} | V _{CEO} = 10V | | 1 | 200 | nA |
| Light current | I _L | V _{CE} = 10V, 200lx ² | 0.5 | 2.0 | 5.0 | mA |
| C - E saturation voltage | V _{CE(sat)} | I _c = 2mA, 2,000lx ² | | 0.2 | 0.4 | V |
| Switching speeds | Rise time | V _{CC} = 10V, I _c = 5mA, R _L = 100 | | 0.8 | | µsec. |
| | Fall time | | | 10 | | µsec. |
| Spectral sensitivity | | | | 500 ~ 1,050 | | nm |
| Peak wavelength | λ _p | | | 880 | | nm |
| Half angle | | | | ± 50 | | deg. |

*2. Color temp. = 2856K standard Tungsten lamp


Photo transistors

ST - 1KA · ST - 1KB


Collector current Vs. Collector - Emitter voltage




Collector current Vs. Illuminance




Dark current Vs. Ambient temperature




Relative sensitivity Vs. Wavelength



Switching time Vs. Load resistance



Radiant Pattern



Collector power dissipation Vs. Ambient temperature

