

L200-0AG-30D

520nm Aqua Green 5mm LEDs

30° viewing angle

52 lumens per Watt
($I_f = 20\text{mA}$, $T_a = 25^\circ\text{C}$)

DWG BY:
LL / JAG
05-11-06

CHK BY:
PL
05-23-06

QA:
GZ
05-31-06


MFG:
—
— — —

REVISION LTR: -
05-11-06

Features:

- High intensity
- 5mm diameter package
- Tinned leads
- Pb-free

Package Dimensions:



Part Number	Chip Material	Lens Color	Emission Color
L200-0AG-30D	InGaN	Water Clear	Super Bright True Green

Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is ± 0.25 mm (.010") unless otherwise noted.
3. Protruded resin under flange is 1.0mm (.04") max.
4. Lead spacing is measured where the leads emerge from the package.
5. Specifications are subject to change without notice.
6. Precautions for ESD: Static electricity and surge can damage the LED. It is recommended to use a wristband or anti-electrostatic glove when handling the LED. All devices, equipment and machinery must be properly grounded.

Absolute Maximum Ratings at Ta=25°C

Parameter	MAX.	Unit
Power Dissipation	80	mW
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100	mA
Continuous Forward Current	20	mA
LED Junction Temperature	100	°C
Derating Linear From 50°C	0.4	mA/°C
Reverse Voltage	5	V
Electrostatic Discharge (ESD)	150	V
Operating Temperature Range	-30°C to +80°C	
Storage Temperature Range	-40°C to +100°C	
Lead Soldering Temperature [4mm (.157") From Body]	260°C for 5 Seconds	

Electrical Optical Characteristics at Ta=25°C


Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	I _V	4500	8500	12000	mcd	I _F =20mA (Note 1)
Viewing Angle	2θ _{1/2}	25	30	35	Deg	(Note 2)
Peak Emission Wavelength	λ _p	517	520	523	nm	I _F =20mA
Dominant Wavelength	λ _d	523	526	529	nm	I _F =20mA (Note 3)
Spectral Line Half-Width	Δλ	---	32	---	nm	I _F =20mA
Forward Voltage	V _F	---	3.2	4.0	V	I _F =20mA
Reverse Current	I _R	---	---	100	μA	V _R =5V
SCP	---	---	0.26	---	cd	I _F =20mA
Lumens	---	---	3.3	---	lm	I _F =20mA
Radiant Intensity	---	---	18000	---	μW/sr	I _F =20mA
Chromaticity Coordinates	x: 0.16 y: 0.72					I _F =20mA

Notes:


- Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
- θ_{1/2} is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- The dominant wavelength (λ_d) is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.
- Forward voltage measurement allowance is ±0.1V
- Luminous Intensity Measurement Allowance is ± 15%.

Typical Electrical / Optical Characteristics Curves
 (25°C Ambient Temperature Unless Otherwise Noted)



Spectral Radiance (Peak @ 520 nm)



Forward Current vs Forward Voltage



Relative Luminous Intensity vs Forward Current



Forward Current Derating Curve

