

SID200N12

NPT IGBT Modules

Characteristics

$T_c = 25^\circ\text{C}$, unless otherwise specified

Symbol	Conditions	min.	typ.	max.	Units
IGBT					
$V_{GE(th)}$	$V_{GE} = V_{CE}$, $I_c = 6\text{mA}$	4.5	5.5	6.5	V
I_{CES}	$V_{GE} = 0$; $V_{CE} = V_{CES}$; $T_j = 25(125)^\circ\text{C}$		0.1	0.3	mA
$V_{CE(TO)}$	$T_j = 25(125)^\circ\text{C}$		1.4(1.6)	1.6(1.8)	V
r_{CE}	$V_{GE} = 15\text{V}$, $T_j = 25(125)^\circ\text{C}$		7.33(10)	9.3(12.6)	$\text{m}\Omega$
$V_{CE(sat)}$	$I_c = 150\text{A}$; $V_{GE} = 15\text{V}$; chip level		2.5(3.1)	3(3.7)	V
C_{ies}	under following conditions		10	13	
C_{oes}	$V_{GE} = 0$, $V_{CE} = 25\text{V}$, $f = 1\text{MHz}$		1.5	2	nF
C_{res}			0.8	1.2	
L_{CE}				20	nH
R_{CC+EE}	res., terminal-chip $T_c = 25(125)^\circ\text{C}$		0.35(0.5)		$\text{m}\Omega$
$t_{d(on)}$	under following conditions: $V_{CC} = 600\text{V}$, $I_c = 150\text{A}$		220	400	ns
t_r	$R_{Gon} = R_{Goff} = 5.6\Omega$, $T_j = 125^\circ\text{C}$		100	200	ns
$t_{d(off)}$	$V_{GE} = \pm 15\text{V}$		600	800	ns
t_f			70	100	ns
$E_{on}(E_{off})$			24(17)		mJ
Inverse Diode under following conditions:					
$V_F = V_{EC}$	$I_F = 150\text{A}$; $V_{GE} = 0\text{V}$; $T_j = 25(125)^\circ\text{C}$		2(1.8)	2.5	V
$V_{(TO)}$	$T_j = 125^\circ\text{C}$			1.2	V
r_T	$T_j = 125^\circ\text{C}$		5	7	$\text{m}\Omega$
I_{RRM}	$I_F = 100\text{A}$; $T_j = 25(125)^\circ\text{C}$		55(80)		A
Q_{rr}	$di/dt = \text{A/us}$		8(20)		μC
E_{rr}	$V_{GE} = V$				mJ
FWD under following conditions:					
$V_F = V_{EC}$	$I_F = 100\text{A}$; $V_{GE} = 0\text{V}$; $T_j = 25(125)^\circ\text{C}$		1.85(1.6)	2.2	V
$V_{(TO)}$	$T_j = 125^\circ\text{C}$			1.2	V
r_T	$T_j = 125^\circ\text{C}$		3	5.5	$\text{m}\Omega$
I_{RRM}	$I_F = 150\text{A}$; $T_j = 25^\circ\text{C}$		60(90)		A
Q_{rr}	$di/dt = \text{A/us}$		8(23)		μC
E_{rr}	$V_{GE} = V$				mJ
Thermal Characteristics					
$R_{th(j-c)}$	per IGBT			0.09	K/W
$R_{th(j-c)D}$	per Inverse Diode			0.25	K/W
$R_{th(j-c)FD}$	per FWD			0.18	K/W
$R_{th(c-s)}$	per module			0.038	K/W
Mechanical Data					
M_s	to heatsink M6	3		5	Nm
M_t	to terminals M6	2.5		5	Nm
w				325	g

