

# Non-Catalog Model

## Power Splitter/Combiner

2 Way-0°

### ADP-2-2-1



CASE STYLE: CD636

#### Important Note

This is a non-catalog model and can be manufactured on specific request. Pricing and delivery information can be supplied upon request.

Please click "Back", and then click "Contact Us" for Applications support.

ELECTRICAL SPECIFICATIONS 50Ω@ +25°C				
Parameter	Min.	Typ.	Max.	Units
Frequency	1		650	MHz
Isolation	20	35		dB
Insertion Loss Above 3.0 dB		0.4	1.0	dB
Phase Unbalance		1.5	4.0	deg.
Amplitude Unbalance		0.2	0.3	dB

MAXIMUM RATINGS	
Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C

PIN CONNECTIONS	
SUM PORT	1
PORT 1	3
PORT 2	4
GND.	ALL OTHERS

#### Electrical Schematic



**Mini-Circuits®**  
ISO 9001 ISO 14001 CERTIFIED

ALL NEW  
minicircuits.com

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: [www.minicircuits.com](http://www.minicircuits.com)

RF/IF MICROWAVE COMPONENTS

REV. OR  
M113463  
ED-7943/1  
ADP-2-2-1  
070917