



Features

- * LOW CURRENT REQUIREMENTS
- * EXCELLENT CHARACTER APPEARANCE
- * HIGH LIGHT OUTPUT
- * RELIABLE AND RUGGED
- * IC COMPATIBLE

Absolute Maximum Ratings at T_A=25°C

REVERSE VOLTAGE PER LED CHIP (<100μ A)	GaAsP RED 3.0V, OTHER 5.0V
D.C. FORWARD CURRENT PER LED CHIP.....	30 mA
PULSE CURRENT (1/10 DUTY CYCLE, 0.1 ms PULSE WIDTH) PER LED CHIP.....	100 mA
OPERATING TEMPERATURE RANGE.....	-25°C TO +85°C
STORAGE TEMPERATURE RANGE.....	-25°C TO +100°C
LEAD SOLDERING TEMP. (1.6mm FROM SEATING PLANE).....	260°C FOR 3 SEC.

Electrical/optical characteristics at T_A=25°C

PART NUMBER		LED CHIP		FACE COLOR		PEAK WAVELENGTH @20mA(nm)	FORWARD VOLTAGE @20mA(V)		LUMINOUS INTENSITY @10mA(mcd)	
CATHODE ROW	ANODE ROW	MATERIAL	EMITTING COLOR	SURFACE	SEGMENT OR DOT		TYP.	MAX.	MIN.	TYP.
DA10-036SR-AEW	DC10-036SR-AEW	GaP	RED	GREY	WHITE	700	2.1	3.0	0.4	0.6
DA10-036SG-AEW	DC10-036SG-AEW	GaP	GREEN	GREY	WHITE	567	2.1	2.6	1.4	2.3
DA10-036SY-AEW	DC10-036SY-AEW	GaAsP ON GaP	YELLOW	GREY	WHITE	585	2.1	3.0	1.1	1.8
DA10-036SO-AEW	DC10-036SO-AEW	GaAsP ON GaP	ORANGE	GREY	WHITE	635	2.1	3.0	1.6	2.6
DA10-036SH-ARR	DC10-036SO-ARR	GaAsP ON GaP	HI-EFF RED	RED	RED	635	2.1	3.0	1.6	2.6

Package Dimensions And Pin Function

COMMON ANODE
PIN NO. FUNCTION

1.COMMON ANODE
2.CATHODE F
3.CATHODE G
4.CATHODE E
5.CATHODE D
6.COMMON ANODE
7.CATHODE DP
8.CATHODE C
9.CATHODE B
10.CATHODE A

COMMON ANODE
PIN NO. FUNCTION

1.COMMON ANODE
2.CATHODE F
3.CATHODE G
4.CATHODE E
5.CATHODE D
6.COMMON ANODE
7.CATHODE DP
8.CATHODE C
9.CATHODE B
10.CATHODE A

1.ALL DIMENSIONS ARE IN mm, TOLERANCE IS ±0.25mm UNLESS OTHERWISE NOTED.
2.THE SLOPE ANGLE OF ANY PIN MAY BE ±5.0°MAX.