



**Micro Commercial Components**

Micro Commercial Components  
 20736 Marilla Street Chatsworth  
 CA 91311  
 Phone: (818) 701-4933  
 Fax: (818) 701-4939

**2SA1015-O  
 2SA1015-Y  
 2SA1015-GR**

**Features**

- Capable of 0.4Watts of Power Dissipation.
- Collector-current 0.15A
- Collector-base Voltage 50V
- Operating and storage junction temperature range: -55°C to +150°C
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Marking:A1015

**PNP Silicon  
 Plastic-Encapsulate  
 Transistor**

**Electrical Characteristics @ 25°C Unless Otherwise Specified**

Symbol	Parameter	Min	Max	Units
--------	-----------	-----	-----	-------

**OFF CHARACTERISTICS**

$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage ( $I_C=0.1mA$ , $I_B=0$ )	50	---	Vdc
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage ( $I_C=100\mu A$ , $I_E=0$ )	50	---	Vdc
$I_{CBO}$	Collector Cutoff Current ( $V_{CB}=50V$ , $I_E=0$ )	---	0.1	$\mu A$
$I_{EBO}$	Emitter Cutoff Current ( $V_{EB}=5.0V$ , $I_C=0$ )	---	0.1	$\mu A$

**ON CHARACTERISTICS**

$h_{FE}$	DC Current Gain ( $I_C=2.0mA$ , $V_{CE}=6.0V$ )	70	400	---
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ( $I_C=100mA$ , $I_B=10mA$ )	---	0.3	Vdc
$V_{BE(sat)}$	Base-Emitter Saturation Voltage ( $I_C=100mA$ , $I_B=10mA$ )	---	1.1	Vdc
$V_{BE}$	Base-Emitter Voltage ( $I_C=310mA$ )	---	1.45	Vdc


**SMALL-SIGNAL CHARACTERISTICS**

$f_T$	Transistor Frequency ( $I_C=1.0mA$ , $V_{CE}=10V$ , $f=30MHz$ )	80	---	MHz
-------	--	----	-----	-----

**CLASSIFICATION OF  $h_{FE}$**

Rank	O	Y	GR
Range	70-140	120-240	200-400

**TO-92**



**DIMENSIONS**

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.170	.190	4.33	4.83	
B	.170	.190	4.30	4.83	
C	.550	.590	13.97	14.97	
D	.010	.020	0.36	0.56	
E	.130	.160	3.30	3.96	
G	.010	.104	2.44	2.64	



Micro Commercial Components™

**\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

**\*\*\*APPLICATIONS DISCLAIMER\*\*\***

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.

---

***www.mccsemi.com***