

Silicon PNP Power Transistors

2SA714

DESCRIPTION


- With TO-3 package
- Wide area of safe operation

APPLICATIONS

- For power amplifier and power switching applications

PINNING(see Fig.2)

| PIN | DESCRIPTION |
|-----|-------------|
| 1 | Base |
| 2 | Emitter |
| 3 | Collector |

**Absolute maximum ratings(Ta=□)**

| SYMBOL | PARAMETER | CONDITIONS | VALUE | UNIT |
|------------------|-----------------------------|---------------------|---------|------|
| V _{CBO} | Collector-base voltage | Open emitter | -150 | V |
| V _{CEO} | Collector-emitter voltage | Open base | -150 | V |
| V _{EBO} | Emitter-base voltage | Open collector | -6 | V |
| I _C | Collector current | | -7 | A |
| I _{CM} | Collector current-peak | | -11 | A |
| P _C | Collector power dissipation | T _C =25□ | 60 | W |
| T _j | Junction temperature | | 150 | □ |
| T _{stg} | Storage temperature | | -55~150 | □ |

Silicon PNP Power Transistors

2SA714

CHARACTERISTICS

T_j=25 °C unless otherwise specified

| SYMBOL | PARAMETER | CONDITIONS | MIN | TYP. | MAX | UNIT |
|----------------------|--------------------------------------|---|------|------|------|------|
| V _{(BR)CEO} | Collector-emitter breakdown voltage | I _C =-25mA ; I _B =0 | -150 | | | V |
| V _{(BR)CBO} | Collector-base breakdown voltage | I _C =-1mA ; I _E =0 | -150 | | | V |
| V _{(BR)EBO} | Emitter-base breakdown voltage | I _E =-1mA ; I _C =0 | -6 | | | V |
| V _{CEsat} | Collector-emitter saturation voltage | I _C =-5A ; I _B =-0.5A | | | -2.0 | V |
| V _{BEsat} | Base-emitter saturation voltage | I _C =-5A ; I _B =-0.5A | | | -2.5 | V |
| I _{CBO} | Collector cut-off current | V _{CB} =-150V ; I _E =0 | | | -0.1 | mA |
| I _{EBO} | Emitter cut-off current | V _{EB} =-6V ; I _C =0 | | | -0.1 | mA |
| h _{FE} | DC current gain | I _C =-1A ; V _{CE} =-5V | 60 | | 320 | |
| f _T | Transition frequency | I _C =-1A ; V _{CE} =-5V | | 8 | | MHz |

Silicon PNP Power Transistors

2SA714

PACKAGE OUTLINE



Fig.2 outline dimensions (unindicated tolerance:±0.1mm)