



October 2006

MMP-M1525-BR-24V Brushed Motor Amplifier Spec Sheet

Performance Characteristics

Peak Power	2.5 kW
Peak Output Voltage	± 100 VDC (shut off @ 125 VDC)
Peak Output Current	± 25 amps (1 sec.)
Max. Continuous Current	± 15 amps (50C), ± 19 amps (25C)
Internal Shunt Regulator	55 W Continuous, 2.4 kW peak for .02 seconds (activates at 190 VDC)

Electrical Characteristics

Input Signal Voltage	± 10 VDC (typ.), ± 35 VDC (max.)
System Gain	0 to 10,000 amps/volt – velocity mode 0 to 10.0 amps/volt – torque mode
Input Impedance	40 k Ohms
Typical Input Drift	10 μ V / Degree C
Bandwidth	2 kHz with 1.2 mH Inductance
Dead Band	Zero

Input Power Requirements

Input Voltage	20 – 100 VDC
---------------	--------------

Adjustments

Peak Current Limit	1 to 25 amps
RMS Current Limit	1 to 19 amps
Signal Command Input	Scaling
Balance	Zero velocity offset
Compensation	System response
Tachometer	Scaling

Diagnostics

Bus Over Voltage	Red LED
Excessive RMS/Over Temp.	Red LED
Surge/Ground Fault	Red LED
Amplifier Operational	Green LED

Physical Characteristics

Module Dimensions (l x w x h)	7.6 in. x 2.5 in. x 4.7 in.
Weight	2.4 lbs
Ambient Temperature	0 C to 50 C
Shutdown Temperature	80 C at heat sink
Relative Humidity	5 – 95% non-condensing

OPTIONS AVAILABLE

MULTIAXIS CONFIGURATIONS
 COMPATIBLE POWER SUPPLIES
 COMPATIBLE SERVOMOTORS, ENCODERS AND GEARMOTORS
 COMPLETE BRUSHED AND BRUSHLESS SYSTEMS

952.955.2626 www.midwestmotion.com eng@midwestmotion.com