

OPA5615

Yellow Green LED Chip

GaP / GaP

1. Material Substrate GaP (N Type)
 Epitaxial Layer GaP (P/N Type)

2. Electrode N (Cathode) Side Gold Alloy
 P (Anode) Side Gold Alloy


3. Electro-Optical Characteristics

Parameter	Symbol	Min	Typ	Max	Unit	Condition
Forward Voltage	$V_{F(1)}$		1.8		V	$I_F=1mA$
	$V_{F(2)}$		2.1	2.4	V	$I_F=20mA$
Reverse Voltage	V_R	6.0			V	$I_R=10\mu A$
Brightness	I_V	300	500		mcd	$I_F=20mA$
Wavelength	Hue		572		nm	$I_F=20mA$
	$\Delta\lambda$		30		nm	$I_F=20mA$

※ Note: Assembled into T1^{3/4} plastic package.

4. Mechanical Data

- (a) Emission Area ----- 12mil × 12mil
- (b) Bottom Area ----- 14mil × 14mil
- (c) Chip Thickness ----- 11mil



Knowledge*on Inc.

For more information, visit our website at www.knowledge-on.com

513-37 Eoyang-dong, Iksan, 570-210, Korea. Tel: +82-63-839-1111. Fax: +82-63-835-8259

