

## HIGH VOLTAGE POWER TRANSISTOR

The BU326 and BU326A Type are a fast switching high voltage transistor, more specially intended for operating in color TV receivers chopper supplies.

### FEATURES:


- \* Collector-Emitter Sustaining Voltage -  
 $V_{CE(sus)} = 375 \text{ V (Min.) - BU326}$   
 $= 400 \text{ V (Min.) - BU326A}$
- \* Low Collector-Emitter Saturation Voltage -  
 $V_{CE(sat)} = 1.5 \text{ V (Max.) @ } I_c = 2.5 \text{ A, } I_B = 0.5 \text{ A}$

### MAXIMUM RATINGS

Characteristic	Symbol	BU326	BU326A	Unit
Collector-Emitter Voltage	$V_{CEO}$	375	400	V
Collector-Base Voltage	$V_{CBO}$	800	900	V
Emitter-Base Voltage	$V_{EBO}$	10		V
Collector Current - Continuous - Peak	$I_c$	6.0 8.0		A
Base Current - Continuous	$I_B$	3.0		A
Total Power Dissipation @ $T_c = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	$P_D$	75 0.428		W W/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	$T_J, T_{STG}$	- 65 to +200		$^\circ\text{C}$


### THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance Junction to Case	$R_{\theta jc}$	2.33	$^\circ\text{C/W}$




**NPN**  
**BU326**  
**BU326A**

**6 AMPERE**  
**POWER**  
**TRANSISTORS**  
**375-400 VOLTS**  
**75 WATTS**



**TO-3**



PIN 1. BASE  
2. EMITTER  
COLLECTOR(CASE)

DIM	MILLIMETERS	
	MIN	MAX
A	38.75	39.96
B	19.28	22.23
C	7.96	9.28
D	11.18	12.19
E	25.20	26.67
F	0.92	1.09
G	1.38	1.62
H	29.90	30.40
I	16.64	17.30
J	3.88	4.36
K	10.67	11.18

**ELECTRICAL CHARACTERISTICS** (  $T_c = 25^\circ\text{C}$  unless otherwise noted )

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

**OFF CHARACTERISTICS**

Collector - Emitter Sustaining Voltage (1) ( $I_C = 100\text{ mA}$ , $I_B = 0$ )	BU326 BU326A	$V_{CEO(SUS)}$	375 400	V
Collector Cutoff Current ( $V_{CE} = 800\text{ V}$ , $V_{BE} = 0$ ) ( $V_{CE} = 900\text{ V}$ , $V_{BE} = 0$ )	BU326 BU326A	$I_{CES}$	1.0 1.0	mA
Emitter Cutoff Current ( $V_{EB} = 10\text{ V}$ , $I_C = 0$ )		$I_{EBO}$	10	mA

**ON CHARACTERISTICS (1)**

DC Current Gain ( $I_C = 1.0\text{ A}$ , $V_{CE} = 5.0\text{ V}$ )		hFE	25(typ)	
Collector - Emitter Saturation Voltage ( $I_C = 2.5\text{ A}$ , $I_B = 0.5\text{ A}$ ) ( $I_C = 4.0\text{ A}$ , $I_B = 1.25\text{ A}$ )		$V_{CE(sat)}$	1.5 3.0	V
Base - Emitter Saturation Voltage ( $I_C = 2.5\text{ A}$ , $I_B = 0.5\text{ A}$ ) ( $I_C = 4.0\text{ A}$ , $I_B = 1.25\text{ A}$ )		$V_{BE(sat)}$	1.4 1.6	V

**DYNAMIC CHARACTERISTICS**


Current Gain - Bandwidth Product ( $I_C = 0.2\text{ A}$ , $V_{CE} = 10\text{ V}$ , $f = 1.0\text{ MHz}$ )		$f_T$	4.0	MHz
--	--	-------	-----	-----

**SWITCHING CHARACTERISTICS**


Turn On Time	$V_{CC} = 250\text{ V}$ , $I_C = 2.5\text{ A}$ $I_{B1} = 0.5\text{ A}$ , $I_{B2} = -1\text{ A}$	$t_{on}$	0.5	us
Storage Time		$t_s$	3.5	us
Fall Time		$t_f$	0.5	us

(1) Pulse Test: Pulse width  $\leq 300\text{ us}$ , Duty Cycle  $\leq 2.0\%$


DC CURRENT GAIN




COLLECTOR SATURATION REGION




BASE-EMITTER VOLTAGE



COLLECTOR-EMITTER VOLTAGE



SWITCHING TIME



SAFE OPERATING AREA

