


NPN Silicon High Voltage Transistors

SXTA 42
SXTA 43

- High breakdown voltage
- Low collector-emitter saturation voltage



Type	Marking	Ordering Code (tape and reel)	Pin Configuration			Package ¹⁾
			1	2	3	
SXTA 42	1D	Q68000-A8394	B	C	E	SOT-89
SXTA 43	1E	Q68000-A8650				

Maximum Ratings

Parameter	Symbol	Values		Unit
		SXTA 42	SXTA 43	
Collector-emitter voltage	V_{CE0}	300	200	V
Collector-base voltage	V_{CB0}	300	200	
Emitter-base voltage	V_{EB0}	6		
Collector current	I_C	500		mA
Total power dissipation, $T_s = 130\text{ °C}$	P_{tot}	1		W
Junction temperature	T_j	150		°C
Storage temperature range	T_{stg}	- 65 ... + 150		

Thermal Resistance

Junction - ambient ²⁾	$R_{th JA}$	≤ 75	K/W
Junction - soldering point	$R_{th JS}$	≤ 20	

1) For detailed information see chapter Package Outlines.

2) Package mounted on epoxy pcb 40 mm × 40 mm × 1.5 mm/6 cm² Cu.

Electrical Characteristics

at $T_A = 25\text{ °C}$, unless otherwise specified.

Parameter	Symbol	Values			Unit
		min.	typ.	max.	

DC characteristics

Collector-emitter breakdown voltage $I_C = 1\text{ mA}$	$V_{(BR)CE0}$	300	–	–	V	
SXTA 42						
SXTA 43		200	–	–		
Collector-base breakdown voltage $I_C = 100\text{ }\mu\text{A}$	$V_{(BR)CB0}$	300	–	–		
SXTA 42						
SXTA 43		200	–	–		
Emitter-base breakdown voltage $I_E = 100\text{ }\mu\text{A}$	$V_{(BR)EB0}$	6	–	–		
Collector cutoff current $V_{CB} = 200\text{ V}, I_E = 0$	I_{CB0}	–	–	100	nA	
SXTA 42						
$V_{CB} = 160\text{ V}, I_E = 0$		SXTA 43	–	–	100	nA
SXTA 43						
$V_{CB} = 200\text{ V}, I_E = 0, T_A = 125\text{ °C}$	SXTA 42	–	–	10	μA	
$V_{CB} = 160\text{ V}, I_E = 0, T_A = 125\text{ °C}$	SXTA 43	–	–	10	μA	
Emitter-base cutoff current $V_{EB} = 6\text{ V}, I_C = 0$	I_{EB0}	–	–	100	nA	
DC current gain $I_C = 1\text{ mA}, V_{CE} = 10\text{ V}$	h_{FE}	25	–	–	–	
$I_C = 10\text{ mA}, V_{CE} = 10\text{ V}$		40	–	–		
$I_C = 30\text{ mA}, V_{CE} = 10\text{ V}$		SXTA 42	40	–		–
SXTA 43		40	–	–		
Collector-emitter saturation voltage ¹⁾ $I_C = 20\text{ mA}, I_B = 2\text{ mA}$	V_{CEsat}	–	–	0.5	V	
SXTA 42						
SXTA 43		–	–	0.4		
Base-emitter saturation voltage ¹⁾ $I_C = 20\text{ mA}, I_B = 2\text{ mA}$	V_{BEsat}	–	–	0.9		


AC characteristics

Transition frequency $I_C = 10\text{ mA}, V_{CE} = 20\text{ V}, f = 100\text{ MHz}$	f_T	50	–	–	MHz
Output capacitance $V_{CB} = 20\text{ V}, f = 1\text{ MHz}$	C_{obo}	–	–	3	pF
SXTA 42					
SXTA 43		–	–	4	

¹⁾ Pulse test conditions: $t \leq 300\text{ }\mu\text{s}$, $D \leq 2\%$.


Total power dissipation $P_{tot} = f(T_A^*; T_S)$

* Package mounted on epoxy




Transition frequency $f_T = f(I_C)$

$V_{CE} = 10\text{ V}, f = 100\text{ MHz}$




Permissible pulse load $P_{tot\ max}/P_{tot\ DC} = f(t_p)$

$T_A = 25\text{ }^\circ\text{C}, D = 0$




Operating range $I_C = f(V_{CE0})$


$T_A = 25\text{ }^\circ\text{C}, D = 0$



Collector cutoff current $I_{CB0} = f(T_A)$
 $V_{CB} = 160 \text{ V}$



Collector current $I_C = f(V_{BE})$
 $V_{CE} = 10 \text{ V}$



DC current gain $h_{FE} = f(I_C)$
 $V_{CE} = 10 \text{ V}$

