

Hex Schmitt trigger


BU4584B / BU4584BF / BU4584BFV

The BU4584B, BU4584BF, and BU4584BFV are inverter-type Schmitt trigger circuits, with six circuits mounted on a single chip. These are ideal when enhanced noise immunity is required, and when wave form rectification circuits with slow rise or fall input times are involved.

●Features

- 1) Low power dissipation.
- 2) Wide range of operating power supply voltage.
- 3) High input impedance.
- 4) High fan-out.
- 5) Direct drive of 2 L-TTL inputs and LS-TTL input.

●Block diagram



●Absolute maximum ratings ($V_{ss} = 0v$, $T_a = 25^{\circ}\text{C}$)

Parameter	Symbol	Limits	Unit
Power supply voltage	V_{DD}	- 0.3 ~ + 18	V
Power dissipation	P_d	1000 (DIP), 450 (SOP), 350 (SSOP)	mW
Operating temperature	T_{opr}	- 40 ~ + 85	$^{\circ}\text{C}$
Storage temperature	T_{stg}	- 55 ~ + 150	$^{\circ}\text{C}$
Input voltage	V_{IN}	- 0.3 ~ $V_{DD} + 0.3$	V

● Electrical characteristics

DC characteristics (unless otherwise noted, $V_{SS} = 0V$, $T_a = 25^\circ C$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	V_{DD} (V)	Conditions	Measurement circuit	
Input high level voltage	V_{IH}	3.5	—	—	V	5	—	Fig.1	
		7.0	—	—		10			
		11.0	—	—		15			
Input low level voltage	V_{IL}	—	—	1.5	V	5	—		
		—	—	3.0		10			
		—	—	4.0		15			
Input high level current	I_{IH}	—	—	0.3	μA	15	$V_{IH} = 15V$		
Input low level current	I_{IL}	—	—	-0.3	μA	15	$V_{IL} = 0V$		
Output high level voltage	V_{OH}	4.95	—	—	V	5	$I_o = 0mA$		
		9.95	—	—		10			
		14.95	—	—		15			
Output low level voltage	V_{OL}	—	—	0.05	V	5	$I_o = 0mA$		
		—	—	0.05		10			
		—	—	0.05		15			
Output high level current	I_{OH}	-0.44	—	—	mA	5	$V_{OH} = 4.6V$		
		-1.1	—	—		10			
		-3.0	—	—		15			
Output low level current	I_{OL}	0.44	—	—	mA	5	$V_{OL} = 0.4V$		
		1.1	—	—		10			
		3.0	—	—		15			
Static current consumption	I_{DD}	—	—	1	μA	5	—	—	
		—	—	2		10			
		—	—	4		5			
Hysteresis voltage	V_H	0.15	—	0.6	V	5	—	Fig.1	
		0.25	—	1.0		10			
		0.40	—	1.5		15			

Switching characteristics (unless otherwise noted, $T_a = 25^\circ C$, $V_{SS} = 0 V$, $C_L = 50pF$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	V_{DD} (V)	Conditions	Measurement circuit
Output rise time	t_{TLH}	—	100	—	ns	5	—	Fig.2
		—	50	—		10		
		—	40	—		15		
Output fall time	t_{THL}	—	100	—	ns	5	—	Fig.2
		—	50	—		10		
		—	40	—		15		
Propagation delay time, "L" to "H"	t_{PLH}	—	125	—	ns	5	—	Fig.2
		—	60	—		10		
		—	50	—		15		
Propagation delay time, "H" to "L"	t_{PHL}	—	125	—	ns	5	—	Fig.2
		—	60	—		10		
		—	50	—		15		

● Measurement circuits





Fig.1 DC characteristics



Input
Output




Fig.2 Switching characteristics

● Electrical characteristic curve





Fig.3 Power dissipation vs. Ta


● External dimensions (Units: mm)

BU4584B




DIP14

BU4584BF



SOP14

BU4584BFV



SSOP-B14