


## POWER MOSFET MODULE


TYPE	I <sub>d</sub> A	V <sub>oss</sub> V	Switching Time(ns)				R <sub>ds(on)</sub> mΩ	V <sub>ds(on)</sub> V	V <sub>ass</sub> V	V <sub>iso</sub> V(RMS)	R <sub>thjc</sub> °C/W	T <sub>j</sub> °C	CONN NO.	Fig. NO.
			t <sub>d(ON)</sub>	t <sub>r</sub>	t <sub>d(OFF)</sub>	t <sub>f</sub>								
FBA50BA50	50	500	60	60	650	130	120	3.0	±20	2500	0.39	150	K	37
FCA50BC50	50	500	60	60	650	130	140	3.5	±20	2500	0.38	150	L	38
FBA75BA50	75	500	60	120	700	210	100	4.0	±20	2500	0.31	150	K	37
FCA75BC50	75	500	60	60	650	130	140	3.5	±20	2500	0.29	150	L	38
SF100AA50	100	500	70	120	1100	280	70	3.5	±20	2500	0.21	150	M	36
SF150AA50	150	500	90	180	1400	360	50	2.5	±20	2500	0.16	150	M	36
SF100AA20	100	200	80	130	650	120	25	1.25	±20	2500	0.41	150	M	36
SF150AA20	150	200	80	240	1300	330	17	1.3	±20	2500	0.27	150	M	36
SF200AA20	200	200	320	560	1800	400	15	1.5	±20	2500	0.2	150	M	36
SF200AA10	200	100	280	220	220	60	8	0.8	±20	2500	0.31	150	M	36



☆ New

## DARLINGTON TRANSISTOR (for IH)



TYPE	I <sub>c</sub> A	V <sub>ceo</sub> V	Switching Time(μs)			h <sub>FE</sub> (min)	V <sub>CE(Sat)</sub> V(max)	V <sub>BE(Sat)</sub> V(max)	I <sub>ceo</sub> mA(max)	T <sub>rr</sub> μS(TYP)	R <sub>thjc</sub> °C/W	T <sub>j</sub> °C	CONN No.	Fig No.
			t <sub>on</sub>	t <sub>s</sub>	t <sub>f</sub>									
SQD35	35	1600	6.5	6	5	35	1.5	2.5	1	3	0.4	150	N	31
SQD50	50	1000	3.5	3	1.75	70	2	2.8	1	2.5	0.36	150	N	31
SQD65	65	750	2.5	3	1.5	200	2	2.8	1	3	0.44	150	N	31
SQD70	70	900	2.5	3	1.45	150	2	2.8	1	3	0.36	150	N	31



● Contact factory

## FAST RECOVERY DIODE

TYPE	V <sub>RRM</sub> V	I <sub>F(AV)</sub>		I <sub>F(RMS)</sub>		I <sub>FSM</sub> A(60Hz)	I <sup>2</sup> T A <sup>2</sup> S	V <sub>FM</sub> V(25°C)	I <sub>RRM</sub> mA(125°C)	V <sub>iso</sub> V(RMS)	t <sub>rr</sub> (ns)	T <sub>j</sub> °C	R <sub>thjc</sub> °C/W	Fig No.	Connection
		A	°C	A	°C										
DG20AA...M	400/600	20	80	31	80	450	840	1.4	6	2500	1200	125	2.0	15	DG,FRG,FRS
FRG25AA	300/600	25	78	38	78	450	840	1.8	30	2500	200	150	1.6	15	
FRG25BA	500	25	94	38	94	450	840	1.4	30	2500	100	150	1.6	15	☆
DD50GB...L	400/600	50	106	78.5	106	1000	4150	1.20	10	2500	700	150	0.7	21	
DD50GB...M	400/600	50	98	78.5	98	1000	4150	1.25	10	2500	800	150	0.7	21	
FRD/FDS100AA	300/600	100	78	157	78	2000	16600	1.8	150	2500	200	150	0.4	21	
FRD/FDS100BA	500	100	94	157	94	2000	16600	1.4	150	2500	100	150	0.4	21	☆
FRS200AA	300/600	200	82	314	92	3300	45000	1.8	300	2500	200	150	0.2	21	
FRS200BA	500	200	94	314	94	3300	45000	1.4	300	2500	100	150	0.2	21	☆
MDF(R)150L	200~400	150	94	235	94	3000	37500	1.3	50	—	450	150	0.3	20	
MDF(R)150M	200~400	150	94	235	94	3000	37500	1.3	50	—	550	150	0.3	20	
MDF(R)250A...L	200~400	250	85	390	85	4500	84000	1.3	60	—	450	150	0.2	20	
MDF(R)250A...M	200~400	250	85	390	85	4500	84000	1.3	60	—	550	150	0.2	20	



☆ Under Develop

## CONNECTION

