

15W Adapter Module Design with OB2262

(Preliminary Release)

www.DataSheet4U.com

Key Features

- Low component count
- Standby Power < 0.2W
- Audio noise free operation
- OCP with line compensation



Version	Date	Revision History
v.1.0	2005-6-23	Preliminary Release

Index

1	Adaptor Module Specification	3
1.1.	Input Characteristic	3
1.2.	Output Characteristic.....	3
1.3.	Performance Spec.....	4
1.4.	Protection Features.....	4
1.5.	Environmental	4
1.6.	Dielectric withstand (Hi-pot) test	4
1.7.	Insulation.....	4
2	Adaptor Module Information	5
2.1	Schematic	5
2.2	PCB Garber File	6
2.3	BOM.....	7
3	Performance Evaluation	9
3.1	Input Characteristics.....	10
3.2	Output Characteristics.....	10
3.3	Protections.....	20
3.4	Brownout/Brownout recovery test	21
3.5	EMI Test.....	22
3.5.1	Conducted EMI Test.....	22
3.5.2	Radiation EMI Test.....	30

Figures

Figure 1	Measured ripple& noise waveform@90Vac/60HZ, no load	11
Figure 2	Measured ripple& noise waveform@90Vac/60HZ, full load	12
Figure 3	Measured ripple& noise waveform@264Vac/50HZ, no load	12
Figure 4	Measured ripple& noise waveform@264Vac/50HZ, full load	13
Figure 5	Measured overshoot waveform@90Vac/60HZ, full load.....	14
Figure 6	Measured overshoot waveform@264Vac/50HZ, full load.....	15
Figure 7	Output voltage waveform of under Dynamic test@264Vac/50HZ,full load.....	15
Figure 8	Output voltage waveform under Dynamic test@90Vac/60HZ with full load	16
Figure 9	Turn on delay time measured waveform@90Vac/60HZ,full load.....	17
Figure 10	Turn on delay time measured waveform@240Vac/50HZ,full load	17
Figure 11	Hold on delay time measured waveform@100Vac/60HZ,full load	18
Figure 12	Rise time measured waveform@100Vac/60HZ,full load.....	18
Figure 13	Rise time measured waveform@240Vac/50HZ,full load.....	19
Figure 14	Fall time measured waveform@100Vac/60HZ,full load	19
Figure 15	Fall time measured waveform@240Vac/50HZ,full load	20

Tables

Table 1 Input characteristic at full load	10
Table 2 Standby power at no load	10
Table 3 Standby power at no load with output LED	10
Table 4 Line Regulation & Load Regulation	10
Table 4 Over shoot/under shoot measurement results	13
Table 5 Output voltage under dynamic test.....	15
Table 6 Turn-on delay /hold-up/Rise/Fall time measurement results.....	16
Table 7 OCP value vs. input voltage	20
Table 8 Brownout/Brownout recovery test results	21

1 Adaptor Module Specification

Model Num: OBPD15W-L120A

Rev. A0

1.1. Input Characteristic

■ AC input voltage rating	100VAC to 240VAC
■ AC input voltage range	90VAC to 264VAC
■ AC input frequency	47HZ to 63HZ
■ Max. In-rush current (At cold Start)	30 A for 100VAC/50HZ at full load 75 A for 240VAC/50HZ at full load
■ Input Current	0.45A (rms) max. @ full load, 100VAC/60HZ 0.23A (rms) max. @ full load, 240VAC/50HZ
■ Leakage Current	0.25mA Max.

1.2. Output Characteristic

■ Output Voltage	+12.0V
■ Output Tolerance	+/-0.6V
■ Min. load current	0A
■ Max. load current	1.25A
■ Line Regulation	1%
■ Load Regulation	5%
■ Ripple & Noise	50 mV

Note: Ripple & Noise is measured with 20MHZ bandwidth limited (peak to peak value) at the end of a 12-inch twisted wire terminated with a 10uF capacitor in parallel with a 0.1uF ceramic capacitor.

1.3. Performance Spec

■ Total Output Power	15W Typical
■ Standby Power	< 0.3W @ 240Vac/50HZ, no load.
■ Efficiency	75% min. @ 90Vac/60HZ with full load
■ Hold up Time	10m sec. min. @ 100Vac/60HZ with full load
■ Turn on Delay Time	1 sec. max. @ 100Vac/60HZ with full load
■ Switching frequency	20K HZ~100K HZ Free-Running.

www.DataSheet4U.com

1.4. Protection Features

■ Short circuit Protection	Output shut down (Auto recovery)
■ Over Voltage Protection	Output shut down when output voltage exceeds 15V
■ Over Current Protection	Output shut down (Auto restart)

1.5. Environmental

■ Operating Temperature	0°C to + 40°C
■ Operating Humidity	20 % to 90 % R. H.
■ Storage Temperature	-40 °C to 85 °C
■ Storage Humidity	0 % to + 90 % R. H.

1.6. Dielectric withstand (Hi-pot) test

■ Input to Output	3000Vac 1 min.
-------------------	----------------

1.7. Insulation

■ Input to Output	DC 500V 10M ohm min.
-------------------	----------------------