


Features


- Design flexibility – Available in a variety sizes and colors to suit most any application.
- Durable Acrylic Panel – Offers sturdy mechanical support and device stability.
- Long lifetimes – Typically 100k hours.
- Low power consumption – Uses far less power than standard incandescent EL or CCFL light sources.

Applications

- Backlighting of LCD Displays
- Panels and Symbols
- Illumination of Large Surface Areas



LED numbers: 12x10=120
 A: ANODE
 K: CATHODE



Electrical and Optical Characteristics (Ta=25°C)

Part Number	PWL nm λP	Material	View Angle 2θ1/2	Luminous Intensity Iv				Forward Voltage VF			
				min.	typ.	max.	IF@	min.	typ.	max.	IF@
MTBL2311-G2	574	InGaAlP	-	-	320.00	-	20mA	-	4.20	-	20mA
-	nm	-	deg	mcd				V			

Company Headquarters
 3 Northway Lane North
 Latham, New York 12110
 Toll Free: 800.984.5337
 Fax: 518.785.4725



Web: www.marktechopto.com | Email: info@marktechopto.com

West Coast Sales Office
 950 South Coast Drive, Suite 225
 Costa Mesa, California 92626
 Toll Free: 800.984.5337
 Fax: 714.850.9314