

# Wireless Bipolar Power Transistor, 2W

## 1.78 - 1.90 GHz

PH1819-2


V2.00

### Features

- Designed for Cellular Base Station Applications
- Class AB: -34 dBc Typ 3rd IMD at 2 Watts PEP
- Class A: +43 dBm Typ 3rd Order Intercept Point
- Common Emitter Configuration
- Internal Input Impedance Matching
- Diffused Emitter Ballasting

### Absolute Maximum Ratings at 25°C

Parameter	Symbol	Rating	Units
Collector-Base Voltage	$V_{CBO}$	65	V
Collector-Emitter Voltage	$V_{CES}$	65	V
Emitter-Base Voltage	$V_{EBO}$	3.0	V
Collector Current	$I_C$	2.0	A
Power Dissipation	$P_D$	13.5	W
Junction Temperature	$T_J$	200	°C
Storage Temperature	$T_{STG}$	-55 to +150	°C
Thermal Resistance	$\theta_{JC}$	13	°C/W




UNLESS OTHERWISE NOTED, TOLERANCES ARE INCHES = .005" (MILLIMETERS = .13MM)

### Electrical Characteristics at 25°C

Parameter	Symbol	Min	Max	Units	Test Conditions
Collector-Emitter Breakdown Voltage	$BV_{CES}$	65	-	V	$I_C=5\text{ mA}$
Collector-Emitter Leakage Current	$I_{CES}$	-	1.0	mA	$V_{CE}=25\text{ V}$
Collector-Emitter Breakdown Voltage	$BV_{CEO}$	22	-	V	$I_C=5\text{ mA}$
Collector-Emitter Breakdown Voltage	$BV_{CER}$	30	-	V	$I_C=5\text{ mA}, R_{BE}=220\ \Omega$
Emitter-Base Breakdown Voltage	$BV_{EBO}$	3.0	-	V	$I_b=5\text{ mA}$
DC Forward Current Gain	$h_{FE}$	15	120	-	$V_{CE}=5\text{ V}, I_C=200\text{ mA}$
Power Gain	$G_p$	10	-	dB	$V_{CC}=25\text{ V}, I_{CO}=25\text{ mA}, P_{OUT}=2.0\text{ W}, F=1.78, 1.85, 1.90\text{ GHz}$
Collector Efficiency	$\eta_c$	35	-	%	$V_{CC}=25\text{ V}, I_{CO}=25\text{ mA}, P_{OUT}=2.0\text{ W}, F=1.78, 1.85, 1.90\text{ GHz}$
Input Return Loss	RL	10	-	dB	$V_{CC}=25\text{ V}, I_{CO}=25\text{ mA}, P_{OUT}=2.0\text{ W}, F=1.78, 1.85, 1.90\text{ GHz}$
Load Mismatch Tolerance	VSWR-T	-	5:1	-	$V_{CC}=25\text{ V}, I_{CO}=25\text{ mA}, P_{OUT}=2.0\text{ W}, F=1.78, 1.85, 1.90\text{ GHz}$
3rd Order IMD	$IMD_3$	-	-32	dBc	$V_{CC}=25\text{ V}, I_{CO}=25\text{ mA}, P_{OUT}=2.0\text{ W PEP}, F=1850\text{ MHz}, \Delta F=100\text{ kHz}$

### Typical Optimum Device Impedances

F(GHz)	$Z_{IN}(\Omega)$	$Z_{LOAD}(\Omega)$
1.78	$6.6 + j10.0$	$6.0 + j12.0$
1.85	$8.4 + j10.1$	$5.7 + j11.0$
1.90	$9.5 + j9.9$	$5.0 + j9.0$



Specifications Subject to Change Without Notice.

M/A-COM, Inc.


North America: Tel. (800) 366-2266  
Fax (800) 618-8883

Asia/Pacific: Tel. +81 (03) 3226-1671  
Fax +81 (03) 3226-1451

Europe: Tel. +44 (1344) 869 595  
Fax +44 (1344) 300 020

9-179

RF Test Fixture



ARTWORK DIMENSIONS IN MILS

PARTS LIST

- C1 C2 C3     33 pF ATC SIZE A
- C4            5000 pF
- C5            4.7 uF 63 VOLTS
- CR1          1N914B DIODE
- Q1            PH1819-2
- R1            5 OHMS 1/4 WATT
- RL1          6T/NO. 24 AWG ON 3 OHM 1/4 WATT
- BOARD TYPE: ROGERS 6010.5 .025' THICK, E<sub>R</sub> = 10.5

Specifications Subject to Change Without Notice.

9-180







M/A-COM, Inc.

North America: Tel. (800) 366-2266  
Fax (800) 618-8883

Asia/Pacific: Tel. +81 (03) 3226-1671  
Fax +81 (03) 3226-1451

Europe: Tel. +44 (1344) 869 595  
Fax +44 (1344) 300 020

Typical Performance Curves



Specifications Subject to Change Without Notice.

M/A-COM, Inc.

North America: Tel. (800) 366-2266  
 Fax (800) 618-8883

Asia/Pacific: Tel. +81 (03) 3226-1671  
 Fax +81 (03) 3226-1451

Europe: Tel. +44 (1344) 869 595  
 Fax +44 (1344) 300 020

9-181

## Typical S-Parameters

 $V_{CC}=25\text{ V}$ ,  $I_{CQ}=200\text{ mA}$ 

f(MHz)	S11		S21		S12		S22	
	Mag	Phase	Mag	Phase	Mag	Phase	Mag	Phase
100	1.10	171.5	23.80	120.3	0.012	-7.4	0.32	-74.5
200	0.75	175.1	12.15	92.1	0.014	-4.7	0.22	-89.6
300	0.79	-177.9	7.79	81.2	0.016	-4.5	0.20	-95.7
400	0.84	-177.4	5.77	74.4	0.016	-9.8	0.23	-98.7
500	0.87	-178.5	4.65	68.4	0.017	-3.7	0.26	-100.5
600	0.89	179.8	3.96	62.6	0.018	-5.9	0.27	-101.4
700	0.89	178.3	3.49	56.7	0.018	-0.7	0.29	-104.4
800	0.91	177.4	3.08	51.1	0.019	-2.7	0.33	-103.3
900	0.91	175.4	2.89	45.4	0.017	-3.4	0.36	-111.0
1000	0.91	174.1	2.74	38.9	0.019	-0.9	0.40	-114.6
1100	0.89	171.5	2.64	28.9	0.024	-6.1	0.46	-117.3
1200	0.87	171.7	2.45	22.8	0.024	-13.6	0.53	-120.8
1300	0.86	170.8	2.35	15.7	0.023	-18.3	0.57	-122.3
1400	0.86	170.3	2.32	7.6	0.026	-21.1	0.63	-145.5
1450	0.85	170.1	2.30	3.4	0.026	-22.9	0.65	-126.2
1500	0.84	169.9	2.27	-1.2	0.025	-22.3	0.66	-127.6
1550	0.83	169.7	2.26	-6.4	0.026	-31.0	0.68	-129.1
1600	0.82	169.7	2.24	-11.5	0.030	-37.3	0.71	-131.9
1650	0.82	170.0	2.22	-16.6	0.029	-43.2	0.72	-133.6
1700	0.81	170.5	2.19	-22.4	0.027	-48.5	0.73	-137.6
1750	0.80	171.1	2.14	-28.4	0.025	-52.2	0.76	-140.1
1800	0.80	171.5	2.11	-35.5	0.026	-60.2	0.76	-143.9
1850	0.80	171.9	2.05	-40.7	0.027	-60.1	0.81	-147.5
1900	0.81	172.6	1.99	-47.4	0.024	-67.1	0.81	-150.1
2000	0.82	173.6	1.83	-60.7	0.024	-80.8	0.86	-155.5
2100	0.84	174.5	1.61	-74.0	0.020	-94.0	0.88	-160.0
2200	0.88	174.2	1.40	-84.6	0.019	-104.7	0.87	-164.5
2300	0.90	173.6	1.21	-94.7	0.016	-128.7	0.86	-168.1

Specifications Subject to Change Without Notice.

9-182

M/A-COM, Inc.

North America: Tel. (800) 366-2266

■ Asia/Pacific: Tel. +81 (03) 3226-1671

■ Europe: Tel. +44 (1344) 869 595