

Choke Coil



STANDARD ELECTRICAL SPECIFICATIONS

Inductance (μH) at 1 kHz, 1 V	Tolerance	DCR Max (Ohms)	Irms (A)	Isat (A)
1.0	± 15 %	0.009	5.30	7.00
1.2	± 15 %	0.010	5.00	6.40
1.5	± 15 %	0.011	4.80	5.70
1.8	± 15 %	0.012	4.60	5.20
2.2	± 15 %	0.013	4.40	4.70
2.7	± 15 %	0.014	4.20	4.30
3.3	± 15 %	0.016	4.00	3.90
3.9	± 15 %	0.170	3.80	3.60
4.7	± 15 %	0.022	3.40	3.30
5.6	± 15 %	0.024	3.20	3.00
6.8	± 15 %	0.026	3.10	2.70
8.2	± 15 %	0.028	3.00	2.50
10	± 15 %	0.033	2.80	2.30
12	± 15 %	0.037	2.60	2.10
15	± 15 %	0.040	2.50	1.90
18	± 15 %	0.044	2.40	1.70
22	± 15 %	0.050	2.20	1.50
27	± 15 %	0.070	1.90	1.40
33	± 15 %	0.075	1.80	1.30
39	± 15 %	0.084	1.70	1.20
47	± 15 %	0.104	1.60	1.10
56	± 15 %	0.130	1.40	0.97
68	± 15 %	0.145	1.30	0.88
82	± 15 %	0.152	1.30	0.80
100	± 15 %	0.208	1.10	0.73
120	± 15 %	0.283	0.94	0.66
150	± 15 %	0.330	0.87	0.60
180	± 15 %	0.362	0.83	0.54
220	± 15 %	0.505	0.70	0.49
270	± 15 %	0.557	0.67	0.45
330	± 15 %	0.650	0.62	0.40
390	± 15 %	0.770	0.57	0.37
470	± 15 %	1.03	0.49	0.34
560	± 15 %	1.14	0.47	0.31
680	± 15 %	1.50	0.41	0.28
820	± 15 %	1.98	0.36	0.26
1000	± 15 %	2.30	0.33	0.23
1200	± 15 %	2.55	0.31	0.21
1500	± 15 %	3.00	0.29	0.19
1800	± 15 %	4.00	0.25	0.18
2200	± 15 %	4.40	0.24	0.16
2700	± 15 %	5.80	0.21	0.14
3300	± 15 %	6.56	0.20	0.13
3900	± 15 %	8.63	0.17	0.12
4700	± 15 %	10.10	0.16	0.11
5600	± 15 %	11.20	0.15	0.10
6800	± 15 %	15.00	0.13	0.09
8200	± 15 %	20.80	0.11	0.08
10000	± 15 %	23.40	0.10	0.08
12000	± 15 %	26.00	0.10	0.07
15000	± 15 %	36.00	0.08	0.06
18000	± 15 %	40.00	0.08	0.06

FEATURES

- Printed circuit mounting (axial leads)
- Protected by polyolefin tubing
- High saturation bobbin used allowing high inductance with low DC resistance
- Pre-tinned leads
- High resistivity core offers very high parallel resistance, resulting in maximum coil performance



RoHS COMPLIANT

ELECTRICAL SPECIFICATIONS

Inductance Range: 1.0 μH to 18000 μH

Inductance Tolerance: ± 15 %

Incremental Current: The typical current at which the inductance will be decreased by 5 % from its initial zero DC value

Temperature Rise: 40 °C Max at I_{rms}

Storage Temperature: - 55 °C to + 125 °C

Operating Temperature: - 55 °C to + 85 °C

MECHANICAL SPECIFICATIONS


Wire: Enamelled copper wire 2-UFW

Core: DRWW ferrite core

Lead: Tinned copper wire

Tube: Shrinkable tube

Varnish: #8562/C



DESCRIPTION				
IHD-2	100 μH	15 %	ER	e3
MODEL	INDUCTANCE VALUE	TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER				
I	H	D	2	E R 1 0 1 L
PRODUCT FAMILY			PACKAGE CODE	INDUCTANCE VALUE
				INDUCTANCE TOLERANCE



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.