

Standard Forks – Non-Insulated Brazed Seam



Product Number†	UPC (054007-)	Wire Range (AWG)	Stud Size	W	C	L	E	Thickness	Barrel Length	Barrel I.D.	Terminals per: Carton	Case
M18-6FX M18-6FK	21858 01150	22-18 22-18	6 6	0.34 0.34	0.29 0.29	0.70 0.70	0.54 0.54	0.030 0.030	0.25 0.25	0.070 0.070	100 —	500 1000
M18-8FX M18-8FK	21866 01152	22-18 22-18	8 8	0.34 0.34	0.29 0.29	0.70 0.70	0.54 0.54	0.030 0.030	0.25 0.25	0.070 0.070	100 —	500 1000
M18-10FX M18-10FK	49599 01154	22-18 22-18	10 10	0.34 0.34	0.29 0.29	0.70 0.70	0.54 0.54	0.030 0.030	0.25 0.25	0.070 0.070	100 —	500 1000
M14-6FX M14-6FK	49622 01516	16-14 16-14	6 6	0.34 0.34	0.29 0.29	0.70 0.70	0.54 0.54	0.030 0.030	0.25 0.25	0.090 0.090	100 —	500 1000
M14-8FX M14-8FK	22534 01518	16-14 16-14	8 8	0.34 0.34	0.29 0.29	0.70 0.70	0.54 0.54	0.030 0.030	0.25 0.25	0.090 0.090	100 —	500 1000
M14-10FX M14-10FK	22542 01520	16-14 16-14	10 10	0.34 0.34	0.29 0.29	0.70 0.70	0.54 0.54	0.030 0.030	0.25 0.25	0.090 0.090	100 —	500 1000
M10-6FK	01972	12-10	6	0.38	0.29	0.73	0.54	0.040	0.25	0.135	—	500
M10-8FX M10-8FK	23581 01973	12-10 12-10	8 8	0.38 0.38	0.29 0.29	0.73 0.73	0.54 0.54	0.040 0.040	0.25 0.25	0.135 0.135	50 —	500 500
M10-10FX M10-10FK	23599 01974	12-10 12-10	10 10	0.38 0.38	0.29 0.29	0.73 0.73	0.54 0.54	0.040 0.040	0.25 0.25	0.135 0.135	50 —	500 500

