

SAW Components

Data Sheet R 2704





SAW Components R 2704
Resonator 315,00 MHz

Data Sheet


Features

- 2-port resonator
- nominal 180°-phase at resonance
- Provides reliable, fundamental mode, quartz frequency stabilization i.e. in transmitters or local oscillators

Terminals

■ Ni, gold plated

SMD Ceramic package QCC8C




Dimensions in mm, approx. weight 0,1 g

Pin configuration

2	Input / Ouptput
6	Output / Input

7 Ground (Input / Output) 3 Ground (Output / Input)

4,8 Ground (case)



Туре	Ordering code	Marking and Package according to	Packing according to		
R2704	B39321-R2704-U310	C61157-A7-A56	F61074-V8070-Z000		

Electrostatic Sensitive Device (ESD)

Maximum ratings

Operable temperature range	T_{A}	-45/+85	°C	
Storage temperature range	$T_{\rm stg}$	-45/+85	°C	
DC voltage	$V_{\rm DC}$	12	V	between any terminals
Source power	P_{s}	0	dBm	



SAW Components R 2704
Resonator 315,00 MHz

Data Sheet

Characteristics

 $\begin{array}{ll} \mbox{Reference temperature:} & T_{\mbox{A}} = 25 \ ^{\circ}\mbox{C} \\ \mbox{Terminating Source impedance:} & Z_{\mbox{S}} = 50 \ \Omega \\ \mbox{Terminating Load impedance:} & Z_{\mbox{L}} = 50 \ \Omega \\ \end{array}$

		min.	typ.	max.	
Center frequency	f _c	314,900	315,000	315,100	MHz
(center frequency between 3 dB points)					
Minimum insertion attenuation	α_{min}	_	9,4	11,0	dB
Phase at f _c	φ	_	160	_	° el.
Loaded quality factor	Q_L	5800	9000	_	
Unloaded quality factor	Q_U	9200	13600	_	
Ageing of f _c		_	_	±50	ppm
Equivalent circuit elements					
Motional capacitance	C_1	_	0,196	_	fF
Motional inductance	L_1	_	1,302	_	μН
Motional resistance	R_1	_	195	_	Ω
Input / Output capacitance	C_0	_	1,3	_	pF
Temperature coefficient of frequency 1)	TC_{f}	_	-0,03	_	ppm/K ²
Turnover temperature	T_0	_	25	_	°C

¹⁾ Temperature dependence of f_c : $f_c(T_A) = f_c(T_0)(1 + TC_f(T_A - T_0)^2)$



Resonator R 2704
Resonator 315,00 MHz

Data Sheet

Published by EPCOS AG Surface Acoustic Wave Components Division, SAW CE AE PD P.O. Box 80 17 09, D-81617 München

© EPCOS AG 2001. All Rights Reserved.

As far as patents or other rights of third parties are concerned, liability is only assumed for components per se, not for applications, processes and circuits implemented within components or assemblies.

The information describes the type of component and shall not be considered as assured characteristics.

Terms of delivery and rights to change design reserved.

For questions on technology, prices and delivery please contact the sales offices of EPCOS AG or the international representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our sales offices.