



# SAW Components

## SAW IF filter

IF Filter for Intercarrier Applications

<b>Series/type:</b>	<b>K 7291 M</b>
<b>Ordering code:</b>	<b>B39389-K7291-M100</b>
Date:	February 19, 2009
Version:	2.0

© EPCOS AG 2009. Reproduction, publication and dissemination of this data sheet, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.



Data Sheet


Application

- Standard: B/G, D/K, M/N
- TV IF filter switchable from B/G, D/K mode to M/N mode
- B/G, D/K mode with Nyquist slope and broad sound shelf for sound carriers at 32.40 MHz and 33.40 MHz
- Reduced group delay predistortion as compared to standard B/G half
- M/N mode with Nyquist slope and sound shelf at 34.40 MHz
- Constant group delay




Features

- Plastic package **SIP5K**
- Approximate weight 1.0 g
- RoHS compatible
- Tinned CuFe alloy terminals



Pin configuration

- 1 Input
- 2 Switching input
- 3 Chip carrier - ground
- 4 Output
- 5 Output



Please read *cautions and warnings and important notes* at the end of this document.


**SAW Components**
**K 7291 M**
**SAW IF filter**
**38.90 MHz**
**Data Sheet**
**Characteristics in B/G, D/K mode (switching pin 2 connected to ground)**

Reference temperature:  $T_A = 25\text{ °C}$   
 Terminating source impedance:  $Z_S = 50\ \Omega$   
 Terminating load impedance:  $Z_L = 2\text{ k}\Omega \parallel 3\text{ pF}$

		min.	typ. @ 25 °C	max.	
<b>Insertion attenuation</b> $\alpha$					
Reference level for the following data	37.40 MHz	15.6	17.1	18.6	dB
<b>Relative attenuation</b> $\alpha_{rel}$					
Picture carrier	38.90 MHz	4.7	5.7	6.7	dB
Color carrier	34.47 MHz	-0.1	0.9	1.9	dB
Sound carrier	32.40 MHz	17.7	19.2	20.7	dB
	33.40 MHz	15.6	17.1	—	dB
Adj. picture carrier	30.90 MHz	46.0	60.0	—	dB
	31.90 MHz	40.0	56.0	—	dB
Adj. sound carrier	40.40 MHz	40.0	52.0	—	dB
	41.40 MHz	40.0	50.0	—	dB
Lower sidelobe	25.00 ... 30.90 MHz	38.0	44.0	—	dB
Upper sidelobe	40.40 ... 45.00 MHz	37.0	43.0	—	dB
<b>Reflected wave signal suppression</b>					
1.2 $\mu$ s ... 6.0 $\mu$ s after main pulse (test pulse 250 ns, carrier frequency 36.50 MHz)		42.0	49.0	—	dB
<b>Feedthrough signal suppression</b>					
1.2 $\mu$ s ... 1.1 $\mu$ s before main pulse (test pulse 250 ns, carrier frequency 37.40 MHz)		—	56.0	—	dB
<b>Group delay predistortion</b> $\Delta\tau$					
(reference frequency 38.90 MHz)					
	36.80 MHz	—	-40	—	ns
	34.47 MHz	—	50	—	ns
<b>Impedance at 37.40 MHz</b>					
Input: $Z_{IN} = R_{IN} \parallel C_{IN}$		—	1.6    13.6	—	k $\Omega$    pF
Output: $Z_{OUT} = R_{OUT} \parallel C_{OUT}$		—	3.2    3.2	—	k $\Omega$    pF
<b>Temperature coefficient of frequency</b> $TC_f$		—	-72	—	ppm/K

Please read *cautions and warnings and important notes* at the end of this document.


**SAW Components**
**K 7291 M**
**SAW IF filter**
**38.90 MHz**
**Data Sheet**
**Characteristics in M/N mode (switching pin 2 connected to pin 1)**

Reference temperature:  $T_A = 25\text{ °C}$   
 Terminating source impedance:  $Z_S = 50\ \Omega$   
 Terminating load impedance:  $Z_L = 2\text{ k}\Omega \parallel 3\text{ pF}$

		min.	typ. @ 25 °C	max.	
<b>Insertion attenuation</b>	$\alpha$				
Reference level for the following data	37.40 MHz	14.4	15.9	17.4	dB
<b>Relative attenuation</b>	$\alpha_{rel}$				
Picture carrier	38.90 MHz	4.8	5.8	6.8	dB
Color carrier	35.32 MHz	0.8	1.8	2.8	dB
Sound carrier	34.40 MHz	17.0	18.5	20.0	dB
Adj. picture carrier	32.90 MHz	40.0	49.0	—	dB
Adj. sound carrier	40.40 MHz	40.0	51.0	—	dB
Lower sidelobe	25.00 ... 32.90 MHz	38.0	44.0	—	dB
Upper sidelobe	40.40 ... 45.00 MHz	33.0	39.0	—	dB
<b>Reflected wave signal suppression</b>					
1.3 $\mu$ s ... 6.0 $\mu$ s after main pulse (test pulse 250 ns, carrier frequency 37.40 MHz)		42.0	50.0	—	dB
<b>Feedthrough signal suppression</b>					
1.2 $\mu$ s ... 1.1 $\mu$ s before main pulse (test pulse 250 ns, carrier frequency 37.40 MHz)		—	50.0	—	dB
<b>Group delay ripple (p-p)</b>	$\Delta\tau$	—	50	—	ns
<b>Impedance at 37.40 MHz</b>					
Input: $Z_{IN} = R_{IN} \parallel C_{IN}$		—	1.3 $\parallel$ 19.6	—	k $\Omega$ $\parallel$ pF
Output: $Z_{OUT} = R_{OUT} \parallel C_{OUT}$		—	3.2 $\parallel$ 3.2	—	k $\Omega$ $\parallel$ pF
<b>Temperature coefficient of frequency</b>	$TC_f$	—	-72	—	ppm/K

Please read *cautions and warnings and important notes* at the end of this document.



SAW Components

K 7291 M

SAW IF filter

38.90 MHz

Data Sheet

Maximum ratings



Operable temperature range	T	-25 / +65	°C	
Storage temperature range	T <sub>stg</sub>	-40 / +85	°C	
DC voltage	V <sub>DC</sub>	5	V	between any terminals
AC voltage	V <sub>pp</sub>	10	V	between any terminals

Please read *cautions and warnings and important notes* at the end of this document.



Data Sheet

Frequency response in B/G, D/K mode



Please read *cautions and warnings and important notes* at the end of this document.



SAW Components


K 7291 M

SAW IF filter


38.90 MHz

Data Sheet

Frequency response B/G, D/K mode



Time domain response B/G, D/K mode





Please read *cautions and warnings and important notes* at the end of this document.



Data Sheet

Frequency response in M/N mode



Please read *cautions and warnings and important notes* at the end of this document.





SAW Components


K 7291 M

SAW IF filter


38.90 MHz

Data Sheet

Frequency response M/N mode



Time domain response M/N mode



Please read *cautions and warnings and important notes* at the end of this document.



<b>SAW Components</b>	<b>K 7291 M</b>
<b>SAW IF filter</b>	<b>38.90 MHz</b>

#### Data Sheet

#### References

<b>Type</b>	K 7291 M
<b>Ordering code</b>	B39389-K7291-M100
<b>Marking and package</b>	C61157-A1-A15
<b>Packaging</b>	F61074-V8067-Z000
<b>Date codes</b>	L_1126
<b>S-parameters</b>	
<b>Soldering profile</b>	S_6001
<b>RoHS compatible</b>	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."

For further information please contact your local EPCOS sales office or visit our webpage at [www.epcos.com](http://www.epcos.com) .

**Published by EPCOS AG**  
**Surface Acoustic Wave Components Division**  
**P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2009. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.

10 February 19, 2009



## Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet ([www.epcos.com/material](http://www.epcos.com/material)). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSSP, CTVS, DSSP, MiniBlue, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseMod, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at [www.epcos.com/trademarks](http://www.epcos.com/trademarks).