



SAW Filters for Mobile Communications

Series/Type: B7633

The following products presented in this data sheet are being withdrawn.

Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B39192B7633D810	B39192B7648L310	2008-11-07	2009-03-31	2009-05-31

For further information please contact your nearest EPCOS sales office, which will also support you in selecting a suitable substitute. The addresses of our worldwide sales network are presented at www.epcos.com/sales.



SAW Components

B7633

BAW duplexer

1880.00 / 1960.00 MHz

Data Sheet




Application

- Low-loss RF duplexer for mobile telephone IS-95 CDMA systems




Features

- Package size 5.0 x 5.0 x 1.35 mm³
- Package code QCS12E
- RoHS compatible
- Approximate weight 0.08 g
- Package for **Surface Mount Technology (SMT)**
- Ni, gold-plated terminals
- Ni-UBM
- Matching network required at TX-port



Pin configuration

- 11 TX input, single ended
- 5 RX output, single ended
- 8 Antenna
- 1, 2, 3, 4, 6 Ground
- 7, 9, 10, 12, 13 Ground



Please read *cautions and warnings and important notes* at the end of this document.



SAW Components

B7633

BAW duplexer

1880.00 / 1960.00 MHz

Data Sheet



Characteristics

Operating temperature range:	T = -30 °C to +85 °C
ANT terminating impedance:	Z _{ANT} = 50 Ω
RX terminating impedance:	Z _{RX} = 50 Ω
TX terminating impedance:	Z _{TX} = 50 Ω

Characteristics TX-ANT					min.	typ. @ 25°C	max.	
Center frequency f _C					—	1880.0	—	MHz
Maximum insertion attenuation α _{max}					—	2.1	3.3	dB
1850.6	...	1853.0	MHz		—	2.6	3.0	dB
1853.0	...	1907.0	MHz		—	2.7	3.5	dB
1907.0	...	1909.4	MHz		—	1.4	2.2	dB
Amplitude ripple (p-p) Δα					—	1.4	2.2	dB
1850.6	...	1909.4	MHz		—	1.4	2.2	dB
Return loss					8.0	10.0	—	dB
TX port	1850.6	...	1909.4	MHz	8.0	10.0	—	dB
ANT port	1850.6	...	1989.4	MHz	6.0	8.0	—	dB
Attenuation α					31	33.5	—	dB
0.3	...	1570.0	MHz		31	33.5	—	dB
1570.0	...	1580.0	MHz		30	32.5	—	dB
1580.0	...	1800.0	MHz		29	31.5	—	dB
1930.6	...	1935.0	MHz		42	51.5	—	dB
1935.0	...	1989.4	MHz		38	41.5	—	dB
2400.0	...	2500.0	MHz		34	36.5	—	dB
2500.0	...	3400.0	MHz		20	28	—	dB
3400.0	...	4400.0	MHz		25	30	—	dB
4400.0	...	5550.0	MHz		5	7.5	—	dB
5550.0	...	5730.0	MHz		5	7.5	—	dB

Please read *cautions and warnings and important notes* at the end of this document.



SAW Components

B7633

BAW duplexer

1880.00 / 1960.00 MHz

Data Sheet



Characteristics

Operating temperature range:	T = -30 °C to +85 °C
ANT terminating impedance:	Z _{ANT} = 50 Ω
RX terminating impedance:	Z _{RX} = 50 Ω
TX terminating impedance:	Z _{TX} = 50 Ω

Characteristics ANT-RX					min.	typ. @ 25°C	max.	
Center frequency				f _C	—	1960.0	—	MHz
Maximum insertion attenuation				α _{max}	—	3.6	4.5 ¹⁾	dB
1930.6 ... 1935.0 MHz								
1935.0 ... 1987.0 MHz								
1987.0 ... 1989.4 MHz								
Amplitude ripple (p-p)				Δα	—	1.4	2.7	dB
1930.6 ... 1989.4 MHz								
Return loss					4.0	5.5	—	dB
RX port	1930.6	...	1989.4	MHz				
ANT port	1850.6	...	1989.4	MHz	6.0	8.0	—	dB
Attenuation				α				
0.3 ... 1770.0 MHz								
1770.0 ... 1850.6 MHz								
1850.6 ... 1905.0 MHz								
1905.0 ... 1909.4 MHz								
2010.0 ... 2070.0 MHz								
2070.0 ... 2750.0 MHz								
2750.0 ... 3350.0 MHz								
3350.0 ... 3500.0 MHz								
3500.0 ... 4500.0 MHz								
4500.0 ... 6000.0 MHz								

¹⁾ 4.0dB for 25°C to 85°C

Please read *cautions and warnings and important notes* at the end of this document.



SAW Components

B7633

BAW duplexer

1880.00 / 1960.00 MHz

Data Sheet



Characteristics TX-RX					min.	typ. @ 25°C	max.	
Isolation between RX and TX								
				α				
0.3	...	1800.0	MHz		57	62	—	dB
1850.6	...	1907.0	MHz		54	58	—	dB
1907.0	...	1909.4	MHz		50	57	—	dB
1930.6	...	1935.0	MHz		44	54	—	dB
1935.0	...	1989.4	MHz		42	44	—	dB
2070.0	...	4200.0	MHz		53	60	—	dB

Please read *cautions and warnings and important notes* at the end of this document.



SAW Components

B7633

BAW duplexer

1880.00 / 1960.00 MHz

Data Sheet



Maximum ratings

Operable temperature range	T	−30 / +85	°C	
Storage temperature range	T _{stg}	−40 / +85	°C	
DC voltage	V _{DC}	3	V	
ESD voltage	V _{ESD}	100 ¹⁾	V	source and load impedance 50 Ω
Input Power at				
1850.6 ... 1909.4 MHz	P _{IN}	29	dBm	CDMA modulated signal
elsewhere	P _{IN}	10	dBm	CW

¹⁾ acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.

Please read *cautions and warnings and important notes* at the end of this document.



SAW Components

B7633


BAW duplexer

1880.00 / 1960.00 MHz


Data Sheet



Frequency Response TX - ANT



Frequency Response TX - ANT (wideband)



Please read *cautions and warnings and important notes* at the end of this document.



SAW Components

B7633


BAW duplexer

1880.00 / 1960.00 MHz


Data Sheet



Frequency Response ANT - RX



Frequency Response ANT - RX (wideband)



Please read *cautions and warnings and important notes* at the end of this document.



SAW Components

B7633


BAW duplexer

1880.00 / 1960.00 MHz


Data Sheet









Frequency Response TX - RX



Frequency Response TX - RX (wideband)



Please read *cautions and warnings* and *important notes* at the end of this document.

**SAW Components****B7633****BAW duplexer****1880.00 / 1960.00 MHz****Data Sheet****Return Loss: S_{11} TX-port** **S_{22} ANT-port** **S_{33} RX-port**

Please read *cautions and warnings and important notes* at the end of this document.

10 August 17, 2006

**SAW Components****B7633****BAW duplexer****1880.00 / 1960.00 MHz**

Data Sheet

**References**

Type	B7633
Ordering code	B39192-B7633-D810
Marking and Package	C61157-A3-A5
Packaging	F61074-V8159-Z000
Date Codes	L_1126
S-Parameters	B7633_NB.s3p B7633_WB.s3p
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG
Surface Acoustic Wave Components Division
P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2006. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.

11 August 17, 2006



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of passive electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of a passive electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of a passive electronic component.
3. The warnings, cautions and product-specific notes must be observed.
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as "hazardous")**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order.
We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, CeraDiode, CSSP, PhaseCap, PhaseMod, SIFI, SIKOREL, SilverCap, SIMID, SIOV, SIP5D, SIP5K, TOPcap, UltraCap, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.