

## Complementary MOSFET Half-Bridge (N- and P-Channel)


PRODUCT SUMMARY			
	$V_{DS}$ (V)	$r_{DS(on)}$ ( $\Omega$ )	$I_D$ (A)
N-Channel	20	0.300 at $V_{GS} = 4.5$ V	1.4
		0.410 at $V_{GS} = 3.0$ V	1.2
P-Channel	- 20	0.640 at $V_{GS} = - 4.5$ V	- 0.96
		0.980 at $V_{GS} = - 3.0$ V	- 0.78

### FEATURES


- 100 %  $R_g$  Tested



**RoHS**  
COMPLIANT



Ordering Information: Si3850ADV-T1-E3 (Lead (Pb)-free)



ABSOLUTE MAXIMUM RATINGS $T_A = 25$ °C, unless otherwise noted				
Parameter	Symbol	N-Channel	P-Channel	Unit
Drain-Source Voltage	$V_{DS}$	20	- 20	V
Gate-Source Voltage	$V_{GS}$	$\pm 12$		
Continuous Drain Current ( $T_J = 150$ °C)	$T_A = 25$ °C	1.4	- 0.96	A
	$T_A = 70$ °C	1.1	- 0.77	
Pulsed Drain Current	$I_{DM}$	3.5	- 2.0	
Continuous Source Current (Diode Conduction) <sup>a</sup>	$I_S$	0.9	- 0.9	
Maximum Power Dissipation (Surface Mounted on FR4 Board)	$T_A = 25$ °C	1.08		W
	$T_A = 70$ °C	0.70		
Operating Junction and Storage Temperature Range	$T_J, T_{stg}$	- 55 to 150		°C

THERMAL RESISTANCE RATINGS			
Parameter	Symbol	N- or P-Channel	Unit
Maximum Junction-to-Ambient (Surface Mounted on FR4 Board, $\pm \leq 10$ sec)	$R_{thJA}$	115	°C/W

Notes:  
Maximum under Steady State condition is 150 °C/W.







<b>SPECIFICATIONS</b> $T_J = 25\text{ }^\circ\text{C}$ , unless otherwise noted							
Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
<b>Static</b>							
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\text{ }\mu\text{A}$	N-Ch	0.6		1.5	V
		$V_{DS} = V_{GS}, I_D = -250\text{ }\mu\text{A}$	P-Ch	-0.6		-1.5	
Gate-Body Leakage	$I_{GSS}$	$V_{DS} = 0\text{ V}, V_{GS} = \pm 12\text{ V}$			$\pm 100$	nA	
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 20\text{ V}, V_{GS} = 0\text{ V}$	N-Ch			1	$\mu\text{A}$
		$V_{DS} = -20\text{ V}, V_{GS} = 0\text{ V}$	P-Ch			-1	
		$V_{DS} = 20\text{ V}, V_{GS} = 0\text{ V}, T_J = 70\text{ }^\circ\text{C}$	N-Ch			10	
		$V_{DS} = -20\text{ V}, V_{GS} = 0\text{ V}, T_J = 70\text{ }^\circ\text{C}$	P-Ch			-10	
On-State Drain Current <sup>b</sup>	$I_{D(on)}$	$V_{DS} = 5\text{ V}, V_{GS} = 4.5\text{ V}$	N-Ch	3.0			A
		$V_{DS} = -5\text{ V}, V_{GS} = -4.5\text{ V}$	P-Ch	-1.5			
Drain-Source On-State Resistance <sup>b</sup>	$r_{DS(on)}$	$V_{GS} = 4.5\text{ V}, I_D = 0.5\text{ A}$	N-Ch		0.240	0.300	$\Omega$
		$V_{GS} = -4.5\text{ V}, I_D = -0.5\text{ A}$	P-Ch		0.510	0.640	
		$V_{GS} = 3.0\text{ V}, I_D = 0.5\text{ A}$	N-Ch		0.325	0.410	
		$V_{GS} = -3.0\text{ V}, I_D = -0.5\text{ A}$	P-Ch		0.780	0.980	
Forward Transconductance <sup>b</sup>	$g_{fs}$	$V_{DS} = 10\text{ V}, I_D = 1\text{ A}$	N-Ch		1.8		S
		$V_{DS} = -10\text{ V}, I_D = -1\text{ A}$	P-Ch		1.1		
Diode Forward Voltage <sup>b</sup>	$V_{SD}$	$I_S = 0.9\text{ A}, V_{GS} = 0\text{ V}$	N-Ch		0.87	1.2	V
		$I_S = -0.8\text{ A}, V_{GS} = 0\text{ V}$	P-Ch		-1.0	-1.3	
<b>Dynamic<sup>b</sup></b>							
Total Gate Charge	$Q_g$	N-Channel $V_{DS} = 10\text{ V}, V_{GS} = 4.5\text{ V}, I_D = 1\text{ A}$	N-Ch		0.95	1.4	nC
Gate-Source Charge	$Q_{gs}$		P-Ch		1.10	1.7	
Gate-Drain Charge	$Q_{gd}$	P-Channel $V_{DS} = -10\text{ V}, V_{GS} = -4.5\text{ V}, I_D = -1\text{ A}$	N-Ch		0.22		nC
			P-Ch		0.28		
Gate Resistance	$R_g$		N-Ch		3.5	5.3	$\Omega$
			P-Ch		10.5	16	
Turn-On Delay Time	$t_{d(on)}$	N-Channel $V_{DD} = 10\text{ V}, R_L = 10\text{ }\Omega$ $I_D \cong 0.9\text{ A}, V_{GEN} = 4.5\text{ V}, R_G = 1\text{ }\Omega$	N-Ch		8	14	ns
Rise Time	$t_r$		P-Ch		13	20	
Turn-Off Delay Time	$t_{d(off)}$	P-Channel $V_{DD} = -10\text{ V}, R_L = 10\text{ }\Omega$ $I_D \cong -0.9\text{ A}, V_{GEN} = -4.5\text{ V}, R_G = 1\text{ }\Omega$	N-Ch		16	25	
			P-Ch		34	50	
Fall Time	$t_f$		N-Ch		20	30	
			P-Ch		18	30	
Body Diode Reverse Recovery Time	$t_{rr}$	$I_F = 0.9\text{ A}, di/dt = 100\text{ A}/\mu\text{s}$	N-Ch		20	30	
		$I_F = -0.9\text{ A}, di/dt = 100\text{ A}/\mu\text{s}$	P-Ch		25	40	
Body Diode Reverse Recovery Charge	$Q_{rr}$	$I_F = 0.9\text{ A}, di/dt = 100\text{ A}/\mu\text{s}$	N-Ch		9	15	nC
		$I_F = -0.9\text{ A}, di/dt = 100\text{ A}/\mu\text{s}$	P-Ch		9	15	

## Notes:






- a. Guaranteed by design, not subject to production testing.  
b. Pulse test; pulse width  $\leq 300\text{ }\mu\text{s}$ , duty cycle  $\leq 2\%$ .

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


## N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted




## N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted




**N-CHANNEL TYPICAL CHARACTERISTICS** 25 °C, unless noted




## P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted




**Output Characteristics**




**Transfer Characteristics**




**On-Resistance vs. Drain Current**



**Capacitance**




**Gate Charge**




**On-Resistance vs. Junction Temperature**


## P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage




Single Pulse Power vs. Junction-to-Ambient



$V_{DS}$  – Drain-to-Source Voltage (V)  
\*  $V_{GS} >$  minimum  $V_{GS}$  at which  $r_{DS(on)}$  is specified

Safe Operating Area

**P-CHANNEL TYPICAL CHARACTERISTICS** 25 °C, unless noted



Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?73789>.





## Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.