



Micro Commercial Components

Micro Commercial Components
 20736 Marilla Street Chatsworth
 CA 91311
 Phone: (818) 701-4933
 Fax: (818) 701-4939

SI2303

Features


- 30V, -2.6A, $R_{DS(ON)}=130m\Omega$ @ $V_{GS}=-10V$
- 30V, -2.0A, $R_{DS(ON)}=180m\Omega$ @ $V_{GS}=-4.5V$
- High dense cell design for extremely low $R_{DS(ON)}$
- Rugged and reliable
- Lead free product is acquired
- SOT-23 Package
- Marking Code: S3
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1

Maximum Ratings @ 25°C Unless Otherwise Specified


Symbol	Parameter	Rating	Unit
V_{DS}	Drain-source Voltage	-30	V
I_D	Drain Current-Continuous	-3	A
I_{DM}	Drain Current-Pulsed ^a	-10	A
V_{GS}	Gate-source Voltage	± 20	V
P_D	Total Power Dissipation	0.25	W
$R_{\theta JA}$	Thermal Resistance Junction to Ambient ^b	500	$^{\circ}C/W$
T_J	Operating Junction Temperature	-55 to +150	$^{\circ}C$
T_{STG}	Storage Temperature	-55 to +150	$^{\circ}C$

P-Channel Enhancement Mode Field Effect Transistor

SOT-23




1. GATE
2. SOURCE
3. DRAIN




DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.110	.120	2.80	3.04	
B	.083	.098	2.10	2.64	
C	.047	.055	1.20	1.40	
D	.035	.041	.89	1.03	
E	.070	.081	1.78	2.05	
F	.018	.024	.45	.60	
G	.0005	.0039	.013	.100	
H	.035	.044	.89	1.12	
J	.003	.007	.085	.180	
K	.015	.020	.37	.51	

Internal Block Diagram



Suggested Solder Pad Layout





Micro Commercial Components







SI2303

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted






Parameter	Symbol	Test Condition	Min	Typ	Max	Units
Off Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D = -10 μ A	-30			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -30V, V _{GS} = 0V			-1	μ A
Gate Body Leakage Current, Forward	I _{GSSF}	V _{GS} = 20V, V _{DS} = 0V			100	nA
Gate Body Leakage Current, Reverse	I _{GSSR}	V _{GS} = -20V, V _{DS} = 0V			-100	nA
On Characteristics^c						
Gate Threshold Voltage	V _{GS(th)}	V _{GS} = V _{DS} , I _D = -250 μ A	-1		-3	V
Static Drain-Source On-Resistance	R _{DS(on)}	V _{GS} = -10V, I _D = -2.6A			130	m Ω
		V _{GS} = -4.5V, I _D = -2.0A			180	m Ω
Forward Transconductance	g _{FS}	V _{DS} = -10V, I _D = -1.7A		2.4		S
Dynamic Characteristics^d						
Input Capacitance	C _{iss}	V _{DS} = -15V, V _{GS} = 0V, f = 1.0 MHz		226		pF
Output Capacitance	C _{oss}			87		pF
Reverse Transfer Capacitance	C _{rss}			19		pF
Switching Characteristics^d						
Turn-On Delay Time	t _{d(on)}	V _{DD} = -15V, I _D = -1A, V _{GEN} = -10V, R _G = 6 Ω , R _L = 15 Ω		9	20	ns
Turn-On Rise Time	t _r			9	20	ns
Turn-Off Delay Time	t _{d(off)}			18	35	ns
Turn-Off Fall Time	t _f			6	20	ns
Total Gate Charge	Q _g	V _{DS} = -15V, I _D = -1.7A, V _{GS} = -10V		5.8	10	nC
Gate-Source Charge	Q _{gs}			0.8		nC
Gate-Drain Charge	Q _{gd}			1.5		nC
Drain-Source Diode Characteristics and Maximum Ratings						
Drain-Source Diode Forward Voltage ^c	V _{SD}	V _{GS} = 0V, I _S = -1.25A			-1.2	V

Notes:
a. Repetitive Rating: Pulse width limited by maximum junction temperature.
b. Surface Mounted on FR4 Board, t < 10 sec.
c. Pulse Test: Pulse Width < 300 μ s, Duty Cycle < 2%.
d. Guaranteed by design, not subject to production testing.

Typical characteristics



Typical characteristics





Micro Commercial Components

Ordering Information

Device (Part Number)-TP	Packing Tape&Reel;3Kpcs/Reel
----------------------------	---------------------------------

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

*****APPLICATIONS DISCLAIMER*****

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.

www.mccsemi.com