


BT134-600B


◆ Features

- With TO-126P package
- PIN DESCRIPTION
 - 1 .main terminal 1
 - 2 .main terminal 2
 - 3. gate
 - tab. main terminal 2
- For use in applications requiring high bidirectional transient and blocking voltage capability and high thermal cycling performance. Typical applications include motor control, industrial and domestic lighting, heating and static switching.



◆ QUICK REFERENCE DATA

| SYMBOL | PARAMETER | VALUE | UNIT | | |
|-------------|--------------------------------------|---------|------|--|---------|
| V_{DRM} | Repetitive peak off-state voltage | 600 | V | | |
| V_{RRM} | Repetitive peak off-state voltage | 600 | V | | |
| $I_{T(AV)}$ | Average on-state current | 2 | A | | |
| I_{TSM} | Non-repetitive peak on-state current | 20 | A | | |
| P_{GM} | Peak gate power | 5 | W | | |
| $P_{G(AV)}$ | Average gate power | 0.5 | W | | |
| T_{stg} | Storage temperature | -45~150 | °C | | |
| T_j | Operating junction temperature | 110 | °C | | TO-126P |



◆ ELECTRICAL CHARACTERISTICS ($T_j = 25^\circ\text{C}$, unless otherwise specified)

| SYMBOL | PARAMETER | CONDITIONS | MIN | MAX | UNIT |
|-----------|-----------------------------------|--|-----|-----|------|
| V_{DRM} | Repetitive peak off-state voltage | $I_D=0.1\text{mA}$ | 600 | | V |
| V_{RRM} | Repetitive peak reverse voltage | $I_D=0.5\text{mA}$ | 600 | | V |
| I_{GT} | Gate trigger current | $V_D=12\text{V}; R_L=100\ \Omega$ T2+ G+ | | 6 | mA |
| | | T2+ G- | | 6 | |
| | | T2- G- | | 6 | |
| | | T2- G+ | 10 | | |
| V_T | On-state voltage | $I_T=4\text{A}$ | | 1.7 | V |
| I_H | Holding current | $I_T=0.1\text{A}; I_{GT}=20\text{mA}$ | | 8 | mA |
| V_{GT} | Gate trigger voltage | $V_D=12\text{V}; R_L=100\ \Omega$ T2+ G+ | | 1.5 | V |
| | | T2+ G- | | 1.5 | |
| | | T2- G- | | 1.5 | |
| | | T2- G+ | 1.8 | | |