



LOW PRESSURE TRANSDUCER FULLY TEMPERATURE COMPENSATED AND CALIBRATED DUAL-IN-LINE PACKAGE

DESCRIPTION


The **SM5650** Series of OEM pressure sensors are fully calibrated, temperature compensated low-pressure sensors in dual in-line packages for printed circuit board mounting. These sensors offer improved performance as well as the option for either constant current or constant voltage excitation.

The **SM5600** Series pressure sensors are constructed by attaching a highly stable piezoresistive pressure sensor chip to a ceramic substrate. Thick film resistors on the ceramic are laser trimmed during manufacturing to provide zero offset calibration, temperature compensation for zero offset, and temperature compensation for sensitivity. In the Model **SM5651**, an additional resistor is trimmed to normalize the output of an external differential amplifier to provide span calibration when the sensor is driven by a constant current supply. In the Model **SM5652**, a constant voltage supply can be used and the normalized output span of each sensor can then be easily amplified.

The model **SM5651** is designed for constant current excitation.

The model **SM5652** is designed for constant voltage excitation.

Various pressure port configurations are available for flexibility in matching this product to specific applications.



FEATURES

- Low pressure (from 0-0.15 PSI FS to 0-3.0 PSI FS)
- Constant voltage and constant current versions
- Easy to use dual in-line package (DIP)
- Span calibration to $\pm 2\%$ for low pressure
- Zero offset calibration
- High performance, stable packaged silicon chip
- Gage and differential pressure configurations
- Wide 0-60° C compensated temperature range

APPLICATIONS

- Medical equipment
- Respiration
- HVAC
- Level detection
- Flow measurement
- Industrial control

CHARACTERISTICS FOR SM5651/SM5652 - SPECIFICATIONS

Test Conditions: Model SM5651 w/excitation = 1.500mA @ 25 °C, Model SM5652 w/excitation = 10.00Vdc @ 25 °C, unless otherwise specified. **All parameters below for differential parts are defined for top side only. All parameters below for gage parts are defined for back side only.**

	Min.	Typ.	Max.	Units	Notes
Excitation					
Current (SM5651)	>0	1.50	3.00	mA	
Voltage (SM5652)	>0	10.00	20.00	V	
Output					
Span (SM5651)	25.0	45.0	75.0	mV	1
Span (SM5652)	24.5	25.0	25.5	mV	1, 2
Zero Offset	-2.00	+0.20	2.00	mV	
Temperature Performance					
TC Span	-0.65	+0.20	0.65	%FS	3
TC Offset	-1.00	+0.20	1.00	%FS	3
Temp Hysteresis	-0.30	+0.05	0.30	%FS	4, 7
Accuracy					
Linearity	-0.30	+0.05	0.30	%FS	5, 7
Repeatability	-0.30	+0.05	0.30	%FS	7
Pressure Hysteresis	-0.30	+0.05	0.30	%FS	7
Sensitivity Matching	-2.00	-0.20	+2.00	%FS	1, 6, 7
Impedance (SM5651)					
Z Input	1.80	3.00	3.80	kΩ	
Z Output	2.70	3.30	3.80	kΩ	
Impedance (SM5652)					
Z Input	4.50	8.00	25.00	kΩ	
Z Output	2.00	2.50	3.80	kΩ	
Temperature Range					
Calibration	+0		+60	°C	3
Operating	-40		+125	°C	7
Storage	-40		+125	°C	7
Dynamic Characteristics					
Die Proof Pressure	10X			FS Pressure	7
Die Burst Pressure	15X			FS Pressure	7

Notes:

- Positive Pressure is defined as entry on the bottom side of the die; gain, during factory calibration, is set using negative pressure
- For the SM5652, 0.15 PSI range, span is 23.75 (min) to 26.25 (max).
- Measured over a temperature range of 22 to 58 °C.
For 0.15 PSI, TC Span=±2.0%FS; TC Offset=±2.0%FS; For 0.3 PSI, TC Span=±0.75%FS
- For 0.30 PSI, Hysteresis=±0.45%FS;
For 0.15 PSI, Hysteresis=±0.65%FS
- Best fit straight line; measured from top-side of die
For 0.30 PSI, Linearity=±0.5%FS;
For 0.15 PSI, Linearity=±2.5%FS
- Sensitivity matching relates to part-to-part matching
For 0.15 PSI, Sensitivity Matching=5.0%FS
- Tested on a sample basis

Model 5651 Pin-out

- 1 -Signal Out
- 2 -Iexc
- 3 +Signal Out*
- 4 +Iexc
- 5 Gainset Resistor
- 6 Gainset Resistor

Model 5652 Pin-Out


- 1 -Signal Out
- 2 -Vexc
- 3 +Signal Out*
- 4 +Vexc
- 5
- 6

*Output increases as pressure is increased on Positive Differential Tube or Absolute Tube

DO NOT connect to unlabeled pins

Pressure Ranges

PSI	5651/ 5652
0.15	001
0.30	003
0.80	008
1.50	015
3.00	030



ORDERING INFORMATION:

Excitation
1: Constant Current
2: Constant Voltage

Pin Configuration
3: Pins opposite direction of tube
5: Surface Mountable Pins opposite side of the tube

Tube Length
L: Long (0.480" ±0.005")
N: No Tube
S: Short (0.330" ±0.005")


Pressure Type
D: Differential (2 Tubes)
G: Gage (1 Tube)

Other configurations available on large orders. Consult SMI for details.

Model Number: **SM5652 - 003 - D - 3 - L**

Pin Configuration: Excitation, Pressure range, Pressure Type, Tube Length

Notes: All dimensions are shown in inches



NOTICE

Information in this document is provided solely to enable software and system implementers to use Silicon Microstructures, Inc. products and/or services. No express or implied copyright licenses are granted hereunder to design or fabricate any silicon-based microstructures based on the information in this document.

Silicon Microstructures, Inc. makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does Silicon Microstructures, Inc. assume any liability arising out of the application or use of any product or silicon-based microstructure, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Parameters that may be provided in Silicon Microstructures, Inc. data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. Silicon Microstructures, Inc. assumes no responsibility for any inaccuracies and/or errors in this publication. All operating parameters, must be validated for each customer application by customer's technical experts. Silicon Microstructures, Inc. does not convey any license under its patent rights nor the rights of others. Silicon Microstructures, Inc. makes no representation that the circuits are free of patent infringement. Silicon Microstructures, Inc. products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Silicon Microstructures, Inc. product could create a situation where personal injury or death may occur. Should Buyer purchase or use Silicon Microstructures products for any such unintended or unauthorized application, Buyer shall indemnify and hold Silicon Microstructures, Inc. and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Silicon Microstructures, Inc. was negligent regarding the design or manufacture of the part. Silicon Microstructures, Inc. reserves the right to make changes without further notice to any products herein

Silicon Microstructures, Inc.TM and the Silicon Microstructures, Inc. logo are trademarks of Silicon Microstructures, Inc. All other service or product names are the property of their respective owners.
© Silicon Microstructures, Inc. 2001-2008. All rights reserved.