

Part Number: SL18 0R712

Ordering Different Lead Types:

Inside Kinked Leads	Not available
Outside Kinked Leads	Use -B after Ametherm's Part #

For example: to order an outside kinked lead use part number SL18 0R712-B



Resistance @ 25°C	0.7 Ω ± 20%
Max Steady State Current Up to 65°C	12.0 A
Max Recommended Energy Rating	120.0 J
Actual Failure Point of Instantaneous Energy	240.0 J
Resistance @ 100 % of Maximum Current	0.020 Ω
Resistance @ 50% of Maximum Current	0.060 Ω
Body Temperature at Maximum Current	180 °C
Dissipation Constant	25 mW/°C
Thermal Time Constant	100 seconds
Material Type	"A"
Maximum Capacitance @ 120/240 VAC	8200 μF/ 2000 μF

D	18.0 ± 1.0 mm
T	5.1 ± 0.5 mm
Lead Diameter	1.0 ± 0.1 mm
S	7.8 ± 1.0 mm
L	38.0 ± 5.0 mm
Coating Run Down Straight Leads	3.0mm Max
B	7.5 ± 1.0 mm
C	3.85 ± .5 mm

Revision Date 12/03/2004

Ametherm, Inc. 3111 N. Deer Run Road #4 Carson City, NV 89701
Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670
www.ametherm.com