


Band Switching Diodes

Description

Silicon Epitaxial Planar Diode Switches

For electric bandswitching in radio and TV tuners in the frequency range of (50 to 1000) MHz. The dynamic forward resistance is constant and very small over a wide range of frequency and forward current. The reverse capacitance is also small and largely independent of the reverse voltage.



17431

Features

- These diodes are also available in SOD323 case with the type designations BA782S-V and BA783S-V.
- Lead (Pb)-free component
- Component in acc. to RoHS 2002/95/EC and WEEE 2002/96/EC



Mechanical Data

Case: SOD123 Plastic case

Weight: approx. 10.3 mg

Packaging Codes/Options:

GS18/10 k per 13" reel (8 mm tape), 10 k/box

GS08/3 k per 7" reel (8 mm tape), 15 k/box

Parts Table

Part	Ordering code	Type Marking	Remarks
BA782-V	BA782-V-GS18 or BA782-V-GS08	R2	Tape and Reel
BA783-V	BA783-V-GS18 or BA783-V-GS08	R3	Tape and Reel

Absolute Maximum Ratings

T_{amb} = 25 °C, unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Reverse voltage		V _R	35	V
Forward continuous current	T _{amb} = 25 °C	I _F	100	mA

Thermal Characteristics

T_{amb} = 25 °C, unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Junction temperature		T _j	125	°C
Storage temperature range		T _{stg}	- 55 to + 125	°C

Electrical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Test condition	Part	Symbol	Min	Typ.	Max	Unit
Forward voltage	$I_F = 100\text{ mA}$		V_F			1000	mV
Leakage current	$V_R = 20\text{ V}$		I_R			50	nA
Dynamic forward resistance	$f = (50\text{ to }1000)\text{ MHz}$, $I_F = 3\text{ mA}$	BA782-V	r_f			0.7	Ω
		BA783-V	r_f			1.2	Ω
	$f = (50\text{ to }1000)\text{ MHz}$, $I_F = 10\text{ mA}$	BA782-V	r_f			0.5	Ω
		BA783-V	r_f			0.9	Ω
Diode Capacitance	$V_R = 1\text{ V}$, $f = 1\text{ MHz}$		C_D			1.5	pF
	$V_R = 3\text{ V}$, $f = 1\text{ MHz}$	BA782-V	C_D			1.25	pF
		BA783-V	C_D			1.2	pF
Series inductance across case			L_S		2.5		nH

Typical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified




Figure 1. Diode Capacitance





Figure 2. Dynamic Forward Resistance vs. Forward Current

Package Dimensions in mm (Inches): SOD123



Document no.: S8-V-3910.01-001 (4)
 Rev. 03 - Date: 08.November.2004
 17432

Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.